

M12F04TL0200

产品名称	M12F04TL0200
公司名称	上海域森自动化科技有限公司
价格	.00/个
规格参数	
公司地址	松江区北松公路5885号4幢
联系电话	021-37761775 17321125655

产品详情

电气和机械性能

行业标准: IEC 61076-2-101

线材外被材料: 聚录乙烯 (PVC)

连接器类型: 单头/双头带线

插头导向: 直头/弯头

适配线规: 22AWG/0.34mm²

连接器胶芯: PVC + GF

外模/壳体: PVC

适用电流: 4 A

连接器导体: 铜镀金

适用电压: 60V

适用温度: -20 ° C ~ + 80 ° C

耦合螺丝/螺母: 铜镀镍

绝缘电阻: 100 M

密封方式: O-型密封圈

导体电阻: 5m

屏蔽: 屏蔽型/非屏蔽

芯线连接方式: 焊接型

防护等级: IP67

M12F04TL0200 M12F04TL0300 M12F04TL0500 M12F04TL1000

M12F04SL0200 M12F04SL0300 M12F04SL0500 M12F04SL1000

M12F05SL0200 M12F05SL0300 M12F05SL0500 M12F05SL1000

M12F05TL0200 M12F05TL0300 M12F05TL0500 M12F05TL1000

M12F08TL0200 M12F08TL0300 M12F08TL0500 M12F08TL1000

M12F08SL0200 M12F08SL0300 M12F08SL0500 M12F08SL1000

M12M04TL0200 M12M04TL0300 M12M04TL0500 M12M04TL1000

M12M04SL0200 M12M04SL0300 M12M04SL0500 M12M04SL1000

M12M05SL0200 M12M05SL0300 M12M05SL0500 M12M05SL1000

M12M05TL0200	M12M05TL0300	M12M05TL0500	M12M05TL1000
M12M08TL0200	M12M08TL0300	M12M08TL0500	M12M08TL1000
M12M08SL0200	M12M08SL0300	M12M08SL0500	M12M08SL1000
M8F03TL0200	M8F03TL0300	M8F03TL0500	M8F03TL1000
M8F03SL0200	M8F03SL0300	M8F03SL0500	M8F03SL1000
M8F04SL0200	M8F04SL0300	M8F04SL0500	M8F04SL1000
M8F04TL0200	M8F04TL0300	M8F04TL0500	M8F04TL1000
M8M03TL0200	M8M03TL0300	M8M03TL0500	M8M03TL1000
M8M03SL0200	M8M03SL0300	M8M03SL0500	M8M03SL1000
M8M04SL0200	M8M04SL0300	M8M04SL0500	M8M04SL1000
M8M04TL0200	M8M04TL0300	M8M04TL0500	M8M04TL1000