

356B21传感器含3米通讯线缆

产品名称	356B21传感器含3米通讯线缆
公司名称	上海持承自动化设备有限公司
价格	134.00/个
规格参数	PCB:10 mV/g 356B21: ± 500 g pk 美国:U.S.A
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

产品详情

356B21传感器含3米通讯线缆

356B21传感器出厂标配、356B21传感器源头供货

English:SI: PERFORMANCE Sensitivity (± 10 %)10 mV/g1.02 mV/(m/s) Measurement Range ± 500 g pk ± 4905 m/s pk Frequency Range (± 5 %) (y or z axis)2 to 10000 Hz2 to 10000 Hz Frequency Range (± 5 %) (x axis)2 to 7000 Hz2 to 7000 Hz Resonant Frequency 55 kHz 55 kHz Broadband Resolution (1 to 10000 Hz)0.004 g rms0.04 m/s rms[2] Non-Linearity 1 % 1 %[1] Transverse Sensitivity 5 % 5 % ENVIRONMENTAL Overload Limit (Shock) ± 10000 g pk ± 98100 m/s pk Temperature Range (Operating)-65 to +250 ° F-54 to +121 ° C[3] Temperature Response See Graph %/ ° F See Graph %/ ° F[2][3] ELECTRICAL Excitation Voltage 18 to 30 VDC 18 to 30 VDC Constant Current Excitation 2 to 20 mA 2 to 20 mA Output Impedance 200 Ohm 200 Ohm Output Bias Voltage 7 to 12 VDC 7 to 12 VDC Discharge Time Constant 0.3 to 1.0 sec 0.3 to 1.0 sec Settling Time (within 10% of bias) <3 sec <3 sec Spectral Noise (1 Hz) 1000 g/ Hz 9810 (m/sec²)/ Hz[2] Spectral Noise (10 Hz) 300 g/ Hz 2943 (m/sec²)/ Hz[2] Spectral Noise (100 Hz) 100 g/ Hz 981 (m/sec²)/ Hz[2] Spectral Noise (1 kHz) 50 g/ Hz 490 (m/sec²)/ Hz[2] PHYSICAL Sensing Element Ceramic Ceramic Sensing Geometry Shear Shear Housing Material Titanium Titanium Sealing Hermetic Hermetic Size - Height 0.4 in 10.2 mm Size - Length 0.4 in 10.2 mm Size - Width 0.4 in 10.2 mm Weight 0.14 oz 4 gm[2] Electrical Connector 8-36 4-Pin 8-36 4-Pin Electrical Connection Position Side Side Mounting Thread 5-40 Female 5-40 Female

All specifications are at room temperature unless otherwise specified.

Product Notes

[1] Zero-based, least-squares, straight line method.[2] Typical.[3] 250 ° F to 325 ° F data valid with HT option only.[4] See PCB Declaration of Conformance PS023 for details.

Accessories:

Supplied 034K10 Cable 10FT Mini 4 Pin To (3) BNC(1)080A Adhesive Mounting Base(1)080A109 Petro Wax(1)081A27 Mounting Stud (5-40 to 5-40)(1)081A90 Mounting stud, 10-32 to 5-40(1)ACS-1T NIST traceable triaxial amplitude response, 10 Hz to upper 5% frequency.(1)M081A27 Metric mounting stud, 5-40 to M3 x 0.50 long(1)

Optional Versions:

(A) Adhesive Mount

ENGLISH SI Accessories:080A90 Quick Bonding Gel(1)080A109 Petro Wax(1)

(HT) High temperature, extends normal operation temperatures

ENGLISH SI Temperature Range -65 to +325 ° F -54 to +163 ° C

(J) Ground Isolated

ENGLISH SI Frequency Range (+5 %) 7000 Hz Weight 0.16 oz 4.5 gm Electrical Isolation >100000000 Ohm Size - Height 0.44 in 11.2 mm Size - Length 0.40 in 10.2 mm Size - Width 0.44 in 11.2 mm Mounting Adhesive Accessories:034K10 Cables(1)080A90 Quick Bonding Gel(1)080A109 Petro Wax(1)