

注塑模具顶针防卡防粘耐无黑印油印专用顶针润滑脂，高温顶针油

产品名称	注塑模具顶针防卡防粘耐无黑印油印专用顶针润滑脂，高温顶针油
公司名称	广州百杰通贸易有限公司
价格	1.00/支
规格参数	品牌:肯天ChemTrend 型号:TCE-100 特点:不在制品表面留油印黑印
公司地址	广东省广州市番禺区大龙街东怡新区一街7号
联系电话	020-84649832 13342861850

产品详情

产品名称：Jost TCE-Grease 300

核心优势：

- 1.符合NSF食品规范
- 2.透明注塑制品表面不留黑印
- 3.模具3万模长周期润滑

附加优势：

- 1.耐温300 ° C
- 2.不留油迹在模具活动部位
- 3.可防止模具顶针出现磨损和卡住现象
- 4.德国进口，品质保证

产品说明：

成分：固态润滑脂。

功能：润滑模具活动部件，同时避免润滑油从模具顶针转移至成品表面。

主要应用：

1. 注塑机模具的滑块和顶针润滑

2. 300 ° C以内的高温润滑

3. 普通零件的润滑以及热电偶/挤出模头的润滑等

典型性能：

颜色	白色，抹于顶针上后变为无色
润滑剂	合成剂，PFPE
稠化剂	有机类
NLGI，DIN 51818	2
基础油粘度 (40 ° C)	500 mm/s
相溶性	与其它种类的基础油不相溶

包装：瓶装，200克每瓶，1公斤每罐

TCE – GREASE 300

High temperature – ejector grease up to +300 ° C (572 ° F) solid free – silicone free

PRODUCT DESCRIPTION

TCE – GREASE 300 is a chemical inert and solid-free High-Tech-Grease.

The product is a special development for the long term lubrication of ejectors in injection molding tools.

Because the product does not contain particles it is suitable for very small tolerances.

TCE – GREASE 300 is resistant against acids, lyes, degassing and solvents.

The product is chemical neutral and does not affect plastics.

Small quantities are enough for a long term lubrication and the strong bonding to the ejectors prevents contamination of the part.

PROPERTIES

- Temperature stable up to 300 ° C (572 ° F)
- No drop point
- NSF-H1 approved – suitable in the food industry
- No transfer to molded parts
- Highest number of shots without reapplication
- Resistant against degassing.

DATA

Colour:	white (colorless on the ejector)
Base oil:	synthetic (PFPE)
Thickener:	organic
NLGI-class (DIN 51818):	2
Base oil viscosity (40 ° C):	500 mm/s
Miscibility:	the product is not miscible with greases made of other base oils
Packaging:	200 g dispenser & 1.000 g can