

# 生产销售哈尔滨节能环保燃气锅炉

产品名称	生产销售哈尔滨节能环保燃气锅炉
公司名称	哈尔滨瑞达伟业工贸有限责任公司
价格	.00/个
规格参数	循环方式:自然循环锅炉 适用燃料:天然气 燃料:燃气锅炉
公司地址	哈尔滨市香坊区珠江路92号101室
联系电话	15945162888

## 产品详情

循环方式	自然循环锅炉	适用燃料	天然气
燃料	燃气锅炉	品牌	立威 中正
型号	WNS0.5-0.7-Y(Q) WNS14-1.0/115/70-Y(Q)	燃烧方式	室燃炉
出口压力	低压	锅炉用途	生活锅炉
适用范围	生产行业、洗浴等	结构形式	卧式
燃料耗量	20		

### 产品介绍：

wns系列卧式内燃炉是我厂技术人员根据国内、外先进技术和经验设计而成的锅壳式卧式三回程湿背燃油（气）锅炉。锅炉运行全自动化，燃料经燃烧器雾化后，形成的火炬充满在全波形炉胆内，并能过炉胆壁传递辐射热，此为第一回程。燃烧产生的高温烟气在燃室内汇聚，转向进入第二回程，即螺纹烟管管束区，经对流换热后，烟气温度逐渐降低后至前烟箱，并在此转向进入第三回程，即光管管束区，随后经后烟箱流入烟囱 本系列蒸汽锅炉能大大提高锅炉效率，节约燃料、降低成本，达到产生高性能、省油（气）、安全的锅炉。

该系列产品均经上海工业锅炉研究所热工测试和国家环保局上海除尘设备检测中心环保测试，各项性能指标均达到设计要求，完全符合国家标准，通过江苏省机械工业厅专家鉴定。一致认为，该产品已达到国内、外先进水平。该系列锅炉具有更人性、更安全的全自动智能控制、锅炉效率高、节能环保、维护方便、经贸耐用等优点。系列型号：

wns0.5-0.7-y(q)	wns1-0.7-y(q)	wns1.5-1.0-y(q)
wns2-1.0-y(q)	wns3-1.25-y(q)	wns4-1.25-y(q)
wns5-1.25-y(q)	wns6-1.25-y(q)	wns8-1.25-y(q)
wns10-1.25-y(q)	wns10-1.57-y(q)	wns12-1.25-y(q)
wns12-1.57-y(q)	wns15-1.25-y(q)	wns15-1.57-y(q)
wns20-1.25-y(q)	wns20-1.57-y(q)	wns0.7-0.7/95/70-y(q)
wns1.4-0.7/95/70-y(q)	wns2.1-1.0/95/70-y(q)	wns2.8-1.0/95/70-y(q)

wns3.5-1.0/95/70-y(q)	wns4.2-1.0/115/70-y(q)	wns5.6-1.0/115/70-y(q)
wns7-1.0/115/70-y(q)	wns10.5-1.0/115/70-y(q)	wns14-1.0/115/70-y(q)

product introduction: the wns series horizontal type internal combustion stove is my factory technical personnel acts according to pot shell type horizontal type three which the home, outside the vanguard technology and the empirical design become cheng shi back fuel oil (gas) boiler. the boiler operation entire automation, the fuel atomizes after the burner, forms the torch fills in the entire corrugated flue, and can the furnace tube wall transmission radiating heat, this for the first return trip. the combustion produces the high temperature haze in burns the indoor gathering, changes enters the second return trip, namely thread flue header control area, after heat convection, before the haze temperature reduces the late arrival gradually the smoke box, and changes in this enters the third return trip, namely fluorescent tube control area, afterward after smoke box inflow chimney this series steam boiler can raise the efficiency of boiler greatly, saves the fuel, to reduce the cost, achieves has the high performance, the province oil (gas), the safe boiler. this serial products passes through the shanghai industry boiler research institute hot working test and the national environmental protection bureau shanghai dedusting equipment examination center environmental protection test, the each performance index achieves the design requirements, conforms to the national standards completely, through jiangsu province mechanical industry hall expert appraisal. believed that this product has achieved domestic, outside the advanced level. this series boiler has the human nature, the safer completely automatic intelligent control, the efficiency of boiler to be higher, the energy conservation environmental protection, the maintenance are convenient, economics and trade durable and so on superior characteristic. series model:  
wns0.5-0.7-y(q) wns1-0.7-y(q) wns1.5-1.0-y(q) wns2-1.0-y(q) wns3-1.25-y(q) wns4-1.25-y(q) wns5-1.25-y(q)  
wns6-1.25-y(q) wns8-1.25-y(q) wns10-1.25-y(q) wns10-1.57-y(q) wns12-1.25-y(q) wns12-1.57-y(q)  
wns15-1.25-y(q) wns15-1.57-y(q) wns20-1.25-y(q) wns20-1.57-y(q) wns0.7-0.7/95/70-y(q) wns1.4-0.7/95/70-y(q)  
wns2.1-1.0/95/70-y(q) wns2.8-1.0/95/70-y(q) wns3.5-1.0/95/70-y(q) wns4.2-1.0/115/70-y(q)  
wns5.6-1.0/115/70-y(q) wns7-1.0/115/70-y(q) wns10.5-1.0/115/70-y(q) wns14-1.0/115/70-y(q)