

# 压力表 威特 客户要求 真空压力表

产品名称	压力表 威特 客户要求 真空压力表
公司名称	山东鲁特食品有限公司
价格	.00/个
规格参数	品牌:威特 型号:客户要求 类型:真空压力表
公司地址	山东省济南市历城区仲宫镇营而大桥9号
联系电话	85979789

## 产品详情

品牌 威特 型号 客户要求  
类型 真空压力表

1. standard dry pressure gauge(1).descriptiondiameter: 10", 8", 6", 5", 4(1/2)", 4", 3(1/2)", 3", 2(1/2)", 2", 1(1/2)"case: plastic, steel, stainless steelwindow: glass, acrylicmovement: brass, stainless steelconnection: bottomconnection: 1/2", 1/4", 3/8", 1/8", bsp, npt, ptaccuracy: 3"--10":1.5-1.0%1(1/2)"--2(1/2)":2.5-1.6%(2) descriptiondiameter: 4", 3", 2(1/2)", 2", 1(1/2)"case: plastic, steel, stainless steelwindow: glass, acrylicmovement: brass, stainless steelconnection: backconnection: 1/2", 1/4", 1/8", 3/8", bsp, npt, ptaccuracy: 3"--4":1.5-1.0%1(1/2)"--2(1/2)":2.5-1.6%2. liquid filled pressure gauge(1) descriptiondiameter: 6", 4", 3", 2(1/2)", 2", 1(1/2)"case: plastic, steel, stainless steelwindow: polycarbonatemovement: brass, stainless steelconnection: bottomconnection: 1/2", 1/4", 1/8", 3/8", bsp, npt, ptaccuracy: 3"--6":1.5-1.0%1(1/2)"--2(1/2)":2.5-1.6%(2) descriptiondiameter: 6", 4", 3", 2(1/2)", 2", 1(1/2)"case: stainless steelwindow: polycarbonatemovement: brass, stainless steelconnection: backconnection: 1/2", 1/4", 1/8", 3/8", bsp, npt, ptaccuracy: 3"--6":1.5-1.0%1(1/2)"--2(1/2)":2.5-1.6%3. oxygen and acetylene gaugedescription:pressure gaugediameter: 2(3/4)", 2(1/2)", 2", 1(1/2)"case: steel body painted colors, brasswindow: polycarbonatemovement: brassconnection: back, bottomconnection: 1/4", 1/8", bsp, npt, ptaccuracy: 1(1/2)"--2(3/4)":2.5-1.6%4. freon pressure gaugedescription:diameter: 4", 3", 2(3/4)", 2(1/2)"case: plastic, steel, stainless steelwindow: polycarbonatemovement: brassconnection: bottom, backconnection: 7/16", sae bsp, npt, pt, 1/8accuracy:3"—4":1.5-1.0%1(1/2)"--2(3/4)":2.5-1.6%5. vacuum pressure gaugedescription:diameter: 10", 8", 6", 4", 3", 2(1/2)", 2", 1(1/2)"case: plastic, steel, stainless steelwindow: glass, acrylicmovement: brass, stainless steelconnection: bottom, backconnection: 1/8", 1/4", 3/8", 1/2", bsp, npt, ptaccuracy:3"—10" : 1.5-1.0%1(1/2)"--2(1/2)":2.5-1.6%6. micro pressure gaugedescription:diameter: 2(1/2)", 3", 4"case: steel, steel chromedrange: 0-500mmaq-5,000mmaqmovement: brass, stainless steelconnection: bottom, center backaccuracy: 1.5-1.0%inlet

thread: 1/8", 1/4", 3/8", npt, bsp, bspt other inlet thread specifications available upon request accuracy: 3%—4": 1.5-1.0% 2(1/2) ": 1.5-1.0% 7. fire gauge diameter: 25", 27", 35" case: chrome brass, plastic range: 0~150psi — 0~6,000psi connection: back accuracy: 3% inlet thread: 1/8", 1/4", npt, bsp, bspt other inlet thread specifications available upon request 8. tire gauge (1) diameter: 1-1/2", 2", 2-1/2" case: plastic range: 0-180psi connection: bottom accuracy: 1.6%, 2.5% inlet thread: 1/8", 1/4", npt, bsp, bspt other inlet thread specifications available upon request (2) range: 2.0-99.5psi, 0.15-7.00 bar display: 1/4" lcd power: 3v lithium battery temperature range: 0-409. bimetal thermometer (1) range: -50~650 case: stainless steel, steel diameter: 2(1/2) ", 3", 4", 5", 6" connection: bottom connection stem diameter: 6-12 stem length: 2(1/2) "~24" or according to customer requirements inlet thread: 1/2", 1/4", 1/8", 3/8", bsp, bspt, npt or according to customer requirements accuracy: 1.6-1% (2) bimetal thermometer range: -50~650 case: stainless steel, steel diameter: 3", 4", 5" connection: center back connection stem diameter: 6-12 stem length: 2(1/2) "~24" or according to customer requirements inlet thread: 1/2", 1/4", 1/8", 3/8", bsp, bspt, npt or according customer requirements accuracy: 1.6-1% 10. pressure thermometer range: -20~+160 c, -50~+550 c (-63~+1022 f) case: stainless steel diameter: 3", 4", 6" temperature probe size: 14x150mm, 14x200mm max pressure: brass material 1.6mpa, stainless steel material 6.3mpa capillary length: <20m ambient temperature: -10~+55 c accuracy: 1.6% inlet thread: 1/8", 1/4", 1/2", 3/8", bsp, bspt, npt or according customers order 11. angular board type thermometer range: -30~+600 c diameter: 4", 6", 8" stem diameter: normal 6.3mm, or according to customers order stem length: 63~150mm accuracy: 1.6% inlet thread: 1/2", 1/4", 1/8", 3/8", bsp, bspt, npt or according customers order lens: v-shaped aluminum scale with black figures, lens front, red or blue reading mercury or kerosene filled tube.