

ADAM-4022T 研华双闭环PID控制器

产品名称	ADAM-4022T 研华双闭环PID控制器
公司名称	深圳市元兴丰电子科技有限公司
价格	100.00/个
规格参数	品牌:研华 型号:ADAM-4022T 产地:台湾
公司地址	深圳市罗湖区
联系电话	18476322303

产品详情

ADAM-4022T 以串行为基础的双闭环PID控制器

通道 : 4

输入电压类型: mA, V, Thermistor, RTD

输入电压范围: 0 to 20 mA, 4 to 20 mA, 0 to 10 V

看门狗计时

Display

Power Supply

Analog Input

Analog Output

General

Digital Input

Digital Output

300 mW

RESISTOR-0125-AADAM-4914V-AEADAM-4011-D2ADAM-4012-DEADAM-4013-DEADAM-4015-BEADAM-4015T-AEADAM-4016-A2EADAM-4117-AEADAM-4017+-CEADAM-4017-D2EADAM-4118-AEADAM-4018+-BEADAM-4018-D2EADAM-4019+-AEADAM-4021-DEADAM-4022T-AEADAM4022TA8001E-TADAM-4024-B1EADAM-4150-AEADAM-4050-DEADAM-4051-BEADAM-4052-BEADAM-4053-AEADAM-4055-BEADAM-4056S-AEADAM-4056SO-AEADAM-4060-DEADAM-4168-AEADAM-4068-BEADAM-4069-AEADAM-4080-DEADAM-4510-DEADAM-4510I-AEADAM-4510S-DEADAM-4520-D2EADAM-4520I-AEADAM-4521-AEADAM-4522-AEADAM-4541-AEADAM-4542+-AEADAM-4561-AEADAM-4562-AEADAM-4500-AEADAM-4501-AEADAM-4502-AEADAM-6015-BEADAM-6017-BEADAM-6018-BEADAM-6022-AEADAM-6024-AEADAM-6024-A1EADAM-6050-BEADAM-6051-BEADAM-6052-BEADAM-6060-BE

2 Open collector to 30V, 30 mA max. load

Channels

Power Dissipation

Logic level 0: close to GND Logic level 1: open

2

Channels

Input Voltage

Yes

Serial: 1.2 km

Serial: From 1,200 to 115.2 k

ASCII command & Modbus/RTU

3000 VDC

RS-485

-25~85 ° C (-13~185 ° F)

5~95 %RH

-10~70 ° C (14~158 ° F)

2 x plug-in terminal block (#14~28 AWG)

System (1.6 second)

Watchdog Timer

Connector

Temperature (Operating)

Humidity

Temperature (Storage)

Interface

Isolation Protection

Communication Protocol

Communication Speed

Comm. Distance

Data Flow Control

0~20 mA, 4~20mA

0~10 V

Channels

Voltage Range

Current Output

92 dB

16-bit

10 samples/second (total)

Yes

Thermistor 3k, 10k RTD (Pt100, 1000)

4 differential

Current Input

Direct Sensor Input

Burn-out Detection

Channel Independent Configuration

Sampling Rates

Resolution

CMR @ 50/60 Hz

10~30 VDC

Power Requirement

Power

LED Indicators