

086E80美国PCB传感器直接报价

产品名称	086E80美国PCB传感器直接报价
公司名称	上海持承自动化设备有限公司
价格	63.00/个
规格参数	PCB:100 mV/lbf 086E80:50 lbf pk 美国: 100 kHz
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

产品详情

086E80美国PCB传感器直接报价

086E80全新特价、086E80传感器详细资料、086E80假一赔百

Miniature Instrumented Impulse Hammer, 0 to 50 lbf

Sensitivity: ($\pm 20\%$) 100 mV/lbf (22.5 mV/N)

Measurement Range: 50 lbf pk (222 N pk)

Hammer Mass: 0.17 oz (4.8 gm)

PERFORMANCE Sensitivity ($\pm 20\%$) 100 mV/lbf 22.5 mV/N [2] Measurement Range 50 lbf pk 222 N pk Resonant Frequency 100 kHz 100 kHz Non-Linearity 1% 1% [1] ELECTRICAL Excitation Voltage 20 to 30 VDC 20 to 30 VDC Constant Current Excitation 2 to 20 mA 2 to 20 mA Output Impedance <100 Ohm <100 Ohm Output Bias Voltage 8 to 14 VDC 8 to 14 VDC Discharge Time Constant 100 sec 100 sec [1] PHYSICAL Sensing Element Quartz Quartz Sealing Epoxy Epoxy Hammer Mass 0.17 oz 4.8 gm [3] Head Diameter 0.25 in 6.3 mm Tip Diameter 0.10 in 2.5 mm Hammer Length 4.2 in 107 mm [3] Electrical Connection Position Side Side Extender Mass Weight 0.044 oz 1.25 gm Electrical Connector 5-44 Coaxial 5-44 Coaxial [4]

All specifications are at room temperature unless otherwise specified.

Product Notes

[1] Typical.[2] Steel tip with no extender mass.[3] With plastic handle attached.[4] With aluminum handle attached.[5] See PCB Declaration of Conformance PS136 for details.

Accessories:

Supplied001A20Case(1)018G10Miniature coaxial cable, vinyl insulation jacket, 10-ft, 5-44 to 10-32 coaxial plug(1)080A109Petro Wax(1)084A13Extender mass(1)084A14Plastic handle assembly(2)084A17Aluminum handle with 5-44 connector(1)084A28Vinyl impact cap, red(3)HCS-2Calibration of Series 086 instrumented impact hammers(1)