# 超高压陶瓷电容器

| | |
|---|---|
| 产品名称 | 超高压陶瓷电容器 |
| 公司名称 | 东莞市汉星电子科技有限公司 |
| 价格 | .60/pcs |
| 规格参数 | |
| 公司地址 | 东莞市南城街道袁屋边社区周溪隆溪路5号高盛科技园二期高盛商务楼12层06室（注册地址） |
| 联系电话 | 13556377850 |

# 产品详情

Specification of High Voltage Ceramic Disc Capacitor

| | | | | |
|---|---|---|---|---|
| Model<br>型号 | CT82-6KV-D12-F9.5-102K | | Color<br>颜色 | |
| Condition of Testing<br>试验条件 | | Frequency<br>频率 | Temperature<br>温度 | |
| | | 1KHZ | 22℃ | |
| Static Capacitance<br>容量 | 1000PF | Outline Size | | |
| Withstand Voltage<br>耐压 | ≥9KV | | | |
| Capacitance Range<br>容量范围 | ±10% | | | |
| Dissipation<br>损耗角 | ≤1% | | | |
| Insulation Resistance<br>绝缘电阻 | ≥100000MΩ | | | |
| Temperature<br>Characteristics | Y5T | | | |

| | | | |
|---|---|---|---|
| 温度特性 | | | |
| Operating Temperature<br><br>工作温度 | -25°C~+85°C | Pitch (F)<br><br>脚距 | 9.5±0.3 |
| Diameter× Thickness<br><br>(MAX)直径厚度 | 12×6mm | Diameter of Lead Wire<br><br>引出线直径 | 0.6±0.0 |
| Length of Encapsulated Lead Wire (MAX)<br><br>包封脚长 | 3 mm | Length of Lead Wire<br><br>引线长度 | 25＋/- 2 |
| Application<br><br>应用 | Indispensable components for high voltage or the UHF instruments, machinery, X-ray m type instrument, medical equipment, aerospace, high voltage generator, anion generator, regulator, electric power equipment, meters, home appliances, electrostatic paint spray eq equipment, detector equipment, many other products and industrial applications. | | |