

Xenus XTL-230-18驱动器少量库存

产品名称	Xenus XTL-230-18驱动器少量库存
公司名称	上海持承自动化设备有限公司
价格	188.00/个
规格参数	COPLEY:18A XTL-23:100-240 VAC 美国:191 x 140 x
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

产品详情

Xenus XTL-230-18

Continuous Current: 6A

The XTL panel is an AC line operated package delivering power up to 6kW. A +24 Vdc input powers control circuits ensuring keep-alive operation. Control interfaces include CANopen as well as traditional analog commands.

Incremental encoder feedback is standard with optional resolver and analog encoder interfaces.

Specifications

CONTINUOUS CURRENT

6A

PEAK CURRENT

18A

SUPPLY VOLTAGE

100-240 VAC

DIMENSIONS

191 x 140 x 64 mm

DIGITAL INPUTS

12

DIGITAL OUTPUTS

4

FEEDBACK

Incremental, Digital Halls, Aux encoder/ encoder out

COMMAND INTERFACE

Step/Direction, Analog, PWM

ENVIRONMENT

Commercial

Accessories

CANopen Network Cable 1' (Model: XTL-NC-01)

CANopen Network Cable 10' (Model: XTL-NC-10)

CANopen Network Kit (Model: XTL-NK)

CANopen Network Terminator (Model: XTL-NT)

DB9 Female to RJ45 Adapter Assembly (Model: XTL-CV)

Edge Filter Accessory (Model: XTL-FA-01)

Edge Filter Connector Kit (Model: XTL-FK)

Heat Sink Kit Low Profile (Model: XTL-HL)

Heat Sink Kit Standard Profile (Model: XTL-HS)

Serial Cable Kit (1 per computer) (to be used with CME2 software only) (Model: SER-CK)

Solder Cup Connector Kit (Model: XTL-CK)

Regen Resistor, 15 Ohms (R10, XEL, XML, XPL, XTL only) (Model: XTL-RA-04)

Regen Resistor, 30 Ohms (R10, XEL, XML, XPL, XTL only) (Model: XTL-RA-03)