

# 工业绝热高温密封材料陶瓷纤维纸【祥雨硅酸铝纤维厂】

产品名称	工业绝热高温密封材料陶瓷纤维纸【祥雨硅酸铝纤维厂】
公司名称	祥雨硅酸铝纤维厂
价格	.00/个
规格参数	耐火温度:1260 ( ) 产地:山东东营
公司地址	中国 山东 东营市东营区 南一路
联系电话	86-05468615291

## 产品详情

耐火温度	1260 ( )	规格	60000*610/1220*0.5/1/2/3/4/5/6 ( mm )
产地	山东东营	品牌	祥雨
产品类别	阻燃纸	材质	硅酸铝
导热系数 ( 常温 )	0.075-0.16	等级	1
低温弯折	1	抗弯强度	1
抗压强度	0.5	拉伸强度	.
使用温度	900-1000	撕裂强度	.
芯材	硅酸铝纤维	形态	纤维状
形状	卷板		

<p>陶瓷纤维纸以陶瓷纤维为主要原料，采用湿法成型工艺制成，具有耐高温、耐化学腐蚀、耐热冲击、低导热系数、高电绝缘强度和高弹性模量等性能。其特点为无石棉、纤维长、渣球少、容重小、强度大、弹性好、便于冲切、缠绕等施工操作。适用于高温下的隔热、保温、密封、电绝缘、吸音、过滤等，可代替石棉制品，是一种高级轻质耐火材料</p>			
--	--	--	--

产品特点：a 低导热率，低热容，良好的隔热性能b良好的化学稳定性，耐侵蚀，电绝缘性好c优良的弹性和柔韧性，便于加工安装d良好的热稳定性，抗热震性e良好的隔音性能，机械强度f不含石棉产品应用：1

隔热密封垫2 电热器具隔热绝缘材料3高温过滤材料4 汽车消音器，排气管的消音隔热材料5 高温窑炉，加热装置壁衬6窑炉砌体膨胀缝，密封材料7窑炉砌体，炉门，顶盖密封

产品分类普通型硅酸铝纤维纸 高铝型硅酸铝纤维纸应用范围隔热密封垫；电热器隔热绝缘材料；汽车消音器，排气管的消音隔热材料；高温过滤材料；膨胀缝密封材料。产品特性低导热系数，低蓄热，良好的隔热性能；高强抗撕扯，高柔韧性；双面光滑，优良的弹性和柔韧性，便于加工，安装；抗热冲击，不含石棉。

产品规格：a分类温度：1000 ，1260 ，1350 b 容重：200kg/m<sup>3</sup> c厚度：0.5, 1, 2, 3, 4, 5,6mm

ceramic fiber paper to ceramic fiber as the main raw material, made of wet forming process, high temperature resistance, chemical corrosion, thermal shock, low thermal conductivity, high dielectric strength and high elastic modulus and other properties.

characterized as non-asbestos, fiber length, the ball less residue, a small bulk density, strength, flexibility, and ease of punching, winding, such as construction operations. applicable to high temperature insulation, thermal insulation, sealing, electrical insulation, sound-absorbing, filtering and so on, can take the place of asbestos products, is an advanced light-weight refractories features: 1. low thermal conductivity, low heat capacity, good thermal insulation performance 2. good chemical stability, erosion resistance, electrical insulation and good 3. excellent elasticity and flexibility, easy installation process 4. good thermal stability, thermal shock resistance 5. good noise performance, mechanical strength 6. does not contain asbestos product applications: 1. insulating gasket 2. electric appliances heat insulation material 3. high-temperature filter materials 4. automobile muffler, the muffler exhaust pipe insulation material 5. high-temperature furnace, heating device wall lining 6. kiln masonry expansion joints, sealing material 7. kilns masonry, door, roof sealing product classification ordinary high aluminum silicate

fiber paper type  
aluminosilicate fiber  
paperapplications 1.  
insulation gasket;2.  
electric heater heat  
insulating material;3.  
automobile muffler, the  
muffler exhaust pipe  
insulation material;4.  
high-temperature filter  
material; 5. expansion  
joints dense  
material.product features  
1. low thermal  
conductivity, low heat  
storage, good heat  
insulation properties;2.  
high-strength tear  
resistance, high flexibility;  
3. double-sided smooth,  
excellent flexibility and  
flexibility, ease of  
processing, installation;4.  
thermal shock, non-  
asbestos.product  
specifications:a  
classification  
temperature: 1000 ,  
1260 , 1350 b bulk  
density: 200kg/m<sup>3</sup>c  
thickness: 0.5, 1, 2, 3, 4,  
5,6 mm