

## 605B01传感器样本资料

产品名称	605B01传感器样本资料
公司名称	上海持承自动化设备有限公司
价格	65.00/个
规格参数	PCB:100 mV 605B01:3.9 oZ 美国: ± 50 g
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

## 产品详情

605B01传感器样本资料

605B01传感器期货8-10周

Biaxial ring-style, industrial, ceramic shear ICP accel, 100 mV/g, 0.5 to 5k Hz, side exit, 3-pin conn., biaxial single point ISO 17025 accredited calibration

Sensitivity: ( ± 20%) 100 mV/g(10.2 mV/(m/s))

Frequency Range: ( ± 3dB) 30 to 300000 cpm(.5 to 5000 Hz)

Sensing Element: Ceramic

Measurement Range: ± 50 g( ± 490 m/s)

Weight: (without cable) 3.9 oz(110.6 gm)

All specifications are at room temperature unless otherwise specified.

### Product Notes

[1] Conversion Factor 1g = 9.81 m/s.[2] Zero-based, least-squares, straight line method.[3] The high frequency tolerance is accurate within ± 10% of the specified frequency.[4] Typical.[5] 1/4-28 has no equivalent in S.I. units.[6] See PCB Declaration of Conformance PS023 for details.

Accessories: Supplied

081A Capt  
68 ive  
mou  
nting  
bolt  
1/4-  
28 x  
.90"

ACS NIS  
-2T T Tr  
acea  
ble Si  
ngle  
Poin  
t Cali  
brati  
on at  
100  
Hz  
for  
Each  
Axis

Optional Versions:

(M) Metric Mount

Accessories:

M08 Capt  
1A68ive  
Mou  
nting  
Bolt

Performance  
Sensitivity 10.2 mV/  
( ± 2 g (m/s  
0 %) )  
Meas ± 50 ± 49  
uremg 0  
ent R m/s  
ange  
Freq 30 to .5 to  
uenc 3000 5000  
y Ra 00 Hz  
nge cpm  
( ± 3  
dB)  
Reso 600 10  
nant kcp kHz  
Freq m

uenc  
y  
Broa 350 g3434  
dban m/se  
d Re c2  
solut  
ion  
(1 to  
1000  
0  
Hz)  
Non  $\pm 1$   $\pm 1$   
-Lin % %  
earit  
y  
Tran 5 5  
svers % %  
e Sen  
sitivit  
y  
Environmental  
Over5000 4905  
load g pk 0  
Limit m/s  
(Sho pk  
ck)  
Tem -65 -54  
peratto to  
ure +250+121  
Rang ° F ° C  
e  
Tem See See  
perat Grap Grap  
ure h %/ h %/  
Resp ° F ° F  
onse  
Encl IP68 IP68  
osur  
e Rat  
ing  
Electrical  
Settli 2. 2.  
ng 0 sec 0 sec  
Time  
(with  
in  
1%  
of  
bias)  
Disc 0. 0.  
harg 3 sec 3 sec

e  
Time  
Cons  
tant  
Excit 18 to 18 to  
ation 28 V 28 V  
Volt DC DC  
age  
Cons 2 to 2 to  
tant 20 20  
Curr mA mA  
ent E  
xcita  
tion  
Out <150 <150  
put I Ohm Ohm  
mpe  
danc  
e  
Out 8 to 8 to  
put 12 V 12 V  
Bias DC DC  
Volt  
age  
Spec 8 g/ 78.5  
tral H (m/s  
Nois z ec2)/  
e (10 H  
Hz) z  
Spec 5 g/ 49.1  
tral H (m/s  
Nois z ec2)/  
e (100 H  
Hz) z  
Spec 4 g/ 39.2  
tral H (m/s  
Nois z ec2)/  
e (1 H  
kHz) z  
Elect >100 >100  
rical 0000 0000  
Isola 00 00  
tion Ohm Ohm  
(Cas  
e)  
Physical  
Size 1.38 34.9  
- Dia in mm  
mete  
r

Size 1.00 25.4  
- Heiin mm  
ght  
Weig3.9 110.  
ht (woz 6 gm  
ithou  
t cabl  
e)  
Mou 1/4- Not  
nting28 Appl  
Thre UNFicabl  
ad e  
Mou 2 to 2.7  
nting5 ft- to  
Torqlb 6.8  
ue Nm  
Sensi Cera Cera  
ng Elmic mic  
eme  
nt  
Sensi Shea Shea  
ng G r r  
eom  
etry  
Hou Stain Stain  
sing less less  
MateSteel Steel  
rial  
Seali Wel Wel  
ng ded ded  
Her Her  
meti meti  
c c  
Elect 3-Pi 3-Pi  
rical n n  
Con MIL MIL  
nect -C-5 -C-5  
or 015 015  
Elect Side Side  
rical  
Con  
necti  
on P  
ositi  
on  
Elect X X  
rical axis axis  
Con  
necti  
ons  
(Pin

A)  
Electrical axis Z  
Con  
necti  
ons  
(Pin  
B)  
Electrical axis Gro  
Con  
necti  
ons  
(Pin  
C)