

# 光学检测式装弹簧机 开放式

产品名称	光学检测式装弹簧机 开放式
公司名称	吉瑞精机股份有限公司G-WAY MACHNERY
价格	.00/个
规格参数	类型:开放式 样式:卧式 品牌:G—WAY
公司地址	中国 浙江 宁波市 浙江省宁波市海曙区环城西路229号
联系电话	86 0574 87163472 13616881979

## 产品详情

类型	开放式	样式	卧式
品牌	G—WAY	型号	OASA-20
别名	光学检测式装弹簧机	用途	油封全自动快速装簧和测量尺寸

### 光学检测式装弹簧机

本机器适用大量的油封与弹簧的组合。

动作步骤：

震动盘将油封送到适当的位置。磁盘将弹簧送到适当的位置。没有传统机器弹簧停留在震动盘轨道上的缺点。汽压缸以极快的速度推动治具将油封与弹簧组合。经由探针检查弹簧装填位置是否正确,并以ccd测量装弹簧后尺寸是否正确。

特点：

高性能机构及机电设计以缩小机身尺寸。本机器采用垂直方向送料及装填，避免弹簧装簧失败。全自动量测内外径，并适用于不同颜色的橡胶零件。自动分离良品与不良品，降低生产成本。操作者键入所需参数及上下限值，测试完成后自动得到一个良品与不良品的统计报告。统计资料可储存于usb装置内。本机器对被检测物提供一个完美重现性，使用者可根据统计数位追踪不良品产生的原因。操作者不需要大量的训练。本机器不同于其他一般的视觉系统，更换产品型式时操作简单维修容易。

model	oasa-20	oasa-40	oasa-50
-------	---------	---------	---------

weight(kgs)	280		
dimensions (cm)	60(l) × 80(w) × 180(h)		
magnet rotator size (mm)	130	130	180
vibrating tray size (mm)	400	400	500
oil seal range (mm)	o.d. 8-20	o.d. 20-40	o.d. 40-50
capacity (pcs/min)	10-15 (approx.)		
inspection field size (mm)	90 x 72		
camera resolution (pixels)	1280 x 1024		
max. part's o.d. (mm)	60		
part's height (mm)	0.8-15		
resolution( μ m)	5		
measurement repeatability ( μ m)	30		
controller	plc + hmi + ccd camera		