

034M35原装线缆5英寸

产品名称	034M35原装线缆5英寸
公司名称	上海持承自动化设备有限公司
价格	8.00/根
规格参数	PCB:-130 to +392 034M35:14 pF/ft 美国:25 pF/ft
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

产品详情

034M35原装线缆5英寸

034M35线缆美国进口过来、034M35线缆经久耐用

4-conductor, shielded cable, 5-ft, 4-pin plug to 4-pin LEMO conn., ferrite bead at the LEMO end

Cable Style: Multi Conductor - Shielded

Number of Conductors: 4

Cable Jacket Material: FEP

Temperature Range: -130 to +392 ° F (-90 to +200 ° C)

Impedance

Number of Conductors 4

Cable Style Multi Conductor - Shielded

Cable Configuration Not Twisted

Environmental
Temperature Range -130 to +392 ° F

Pull Strength 20 lb

Electrical
Capacitance (conductor to conductor @ 70 ° F (21 ° C)) 14 pF/ft

Capacitance (conductor to shield / drain @ 70 ° F (21 ° C)) 25 pF/ft

Voltage Rating (rms - maximum) 160 V

Noise Level (pk - pk) <30 mV

Physical
Cable Jacket Diameter 0.077 in

Cable Jacket Material FEP

Cable Jacket Color Blue

Conductor Style Solid

Conductor Material Silver Plated Copper

Conductor Diameter (34 AWG) .006 in

Insulation Material Over Conductor(s)	Extruded PTFE
Shield Type Over Conductor(s)	Braid: 90% Minimum Coverage
Shield Material Over Conductor(s)	Silver Plated Wire
Shield Wire Diameter Over Conductor(s) (Each Strand 40 0.063 in AWG)	
Low Noise Barrier Material	Graphite Impregnated PTFE Tape
Bend Radius (minimum)	1 in
Weight	0.09 oz/ft