

单螺杆失重秤，失重式计量秤

产品名称	单螺杆失重秤，失重式计量秤
公司名称	滁州沛克机械有限公司
价格	50000.00/台
规格参数	品牌:沛克 型号:FW48 精度:千分之五
公司地址	苏滁现代产业园清流东路2855号
联系电话	13260713283

产品详情

一、单螺杆失重式计量秤 Single screw type

1、应用范围 Application field

树脂颗粒、片状颗粒、絮状料、颗粒混合料 Resin granules, flack, flocculus, blendings.

2、产品特点 Features

(1) 悬臂吊带矩阵式秤架，重心低、振动小、抗干扰 Frame Weighing platform, low barycenter, weak vibration, safe accuracy control

(2) 不锈钢波纹管传感器，长久使用形变小、带保护套装，胜任恶劣化工环境

Stainless steel bellows sensor, slight deformation even after long-time use. With protection system, qualified at hard chemical line.

(3) 内镜面料斗，四立面全垂直无收角，物料不易架桥 Mirror Hopper, U shaped hopper, Material is not easy to bridge

(4) 称重信号数字式传输、抗干扰无衰减 Digital transmission of weight data guarantees precise and stable feed control.

(5) 预留搅拌接口 Mixing device connection is prepared.

3、技术参数 Parameter

参 数Parameters	FW-48	FW-63	FW-89	FW-114
型号 型号Model				
流量范围Capacity range	20-100kg/h	50-300kg/h	100-600kg/h	300-1500kg/h
料斗容积Volume	40L	100L	150L	250L
传感器量程Range	50kg	100kg	150kg	200kg
重量Net Weight	86kg	140kg	170kg	190kg
外形(长x宽x高)Size	550x340x680	680x430x900	790x480x1050	950x530x1270
电源Power	AC380V 3相 喂料0.25kw +搅拌0.15kw	AC380V 3相 喂料0.37kw +搅拌0.2kw	AC380V 3相 喂料0.55kw +搅拌0.4kw	AC380V 3相 喂料0.75kw +搅拌0.75kw
输出方式Screw	弹簧或实心单螺杆 Granule Screw			
动态相对误差Dyna mic accuracy	± 0.5%			
最小重量分辨率Min .sensitivity	1g	2g		
出料筒规格Discharg e tube	48x3	63x3	89x3	114x3

1、流量范围值以堆积密度=0.6g/ml物料作测试

Capacity range value is calculated based on materials with stacking density 0.6g/m

2、动态相对误差值以非补料状态大于30秒的采样周期作测试

Dynamic accuracy vale is tested based on working condition status longer than at least 30 seconds.