

双螺杆失重秤

产品名称	双螺杆失重秤
公司名称	滁州沛克机械有限公司
价格	50000.00/台
规格参数	品牌:沛克 型号:FT-38 精度:千分之五
公司地址	苏滁现代产业园清流东路2855号
联系电话	13260713283

产品详情

1、产品特点 Features

(1) 悬臂吊带矩阵式秤架，重心低、振动小、抗干扰Frame Weighing platform, low barycenter, weak vibration, safe accuracy control

(1) 不锈钢波纹管传感器，长久使用形变小、带保护套装，胜任恶劣化工环境

Stainless steel bellows sensor, slight deformation even after long-time use. With protection system, qualified at hard chemical line.

(2) 内镜面料斗，四立面全垂直无收角，物料不易架桥 Mirror Hopper, U shaped hopper, Material is not easy to bridge

(3) 称重信号数字式传输、抗干扰无衰减 Digital transmission of weight data guarantees precise and stable feed control.

2、技术参数 Parameter

参 数	FT-28	FT-38	FT-46	FT-64
Parameters				
型号				
型号Model				
流量范围Capacity range	20-100kg/h	50-300kg/h	100-600kg/h	200-1200kg/h
料斗容积Volume	40L	100L	150L	250L
传感器量程Range	50kg	100kg	150kg	200kg
重量Net Weight	86kg	140kg	170kg	190kg
外形(长x宽x高)Size	550x340x680	680x430x900	790x480x1050	950x530x1270
电源Power	AC380V 3相 喂料0.25kw +搅拌0.15kw	AC380V 3相 喂料0.37kw +搅拌0.2kw	AC380V 3相 喂料0.55kw +搅拌0.4kw	AC380V 3相 喂料0.75kw +搅拌0.75kw
输出方式Screw	实心双螺杆Twin Concave			
动态相对误差Dynamic accuracy	± 0.5%			
最小重量分辨率 Min.sensitivity	1g	2g		
出料筒规格 Discharge tube	45x3x2	57x3x2	65x3x2	89x3x2

1、流量范围值以堆积密度=0.6g/ml物料作测试

Capacity range value is calculated based on materials with stacking density 0.6g/m

2、动态相对误差值以非补料状态大于30秒的采样周期作测试

Dynamic accuracy vale is tested based on working condition status longer than at least 30 seconds.