

# 布拉本达柔性拍打料斗失重秤

产品名称	布拉本达柔性拍打料斗失重秤
公司名称	滁州沛克机械有限公司
价格	60000.00/台
规格参数	特点:柔性料斗拍打式 精度:千分之五 应用:湿度大粉料
公司地址	苏滁现代产业园清流东路2855号
联系电话	13260713283

## 产品详情

### 1、产品特点 Features

搅拌单元不接触物料. No direct touch between stirring unit and materials.

搅拌动作更加轻柔，不破坏物料的原形特征. Light stirring, no damage to the materials.

提高料斗中物料的流动性、优化螺杆填充度、使流速更加稳定. Improve material flow and optimize dynamic loadings of the screws.

目前国际上解决粉料失重喂料的最好方案 Ideal and leading solution and design of powder lose-in-weight feeders

### 2、技术参数 Parameter

参 数Parameters	FP-48	FP-63	FP-76	FP-89
型号				
型号Model				
流量范围Capacity range	20-100kg/h	50-300kg/h	100-600kg/h	200-1200kg/h
料斗容积Volume	40L	100L	200L	250L
传感器量程Range	50kg	100kg	250kg	300kg

重量Net Weight	86kg	140kg	170kg	200kg
外形(长x宽x高)Size	550x340x680	680x430x900	790x480x1050	820x490x1150
电源Power	AC380V 3相 喂料0.25kw  +搅拌0.15kw	AC380V 3相 喂料0.37kw  +搅拌0.2kw	AC380V 3相 喂料0.55kw  +搅拌0.4kw	
输出方式	弹簧或实心单螺杆 Granule Screw			
动态相对误差Dynamic accuracy	± 0.5%			
最小重量分辨率Min .sensitivity	1g	2g		
出料筒规格Discharge tube	48x3	63x3	76x3	89x3

1、流量范围值以堆积密度=0.6g/ml物料作测试

Capacity range value is calculated based on materials with stacking density 0.6g/m

2、动态相对误差值以非补料状态大于30秒的采样周期作测试

Dynamic accuracy vale is tested based on working condition status longer than at least 30 seconds.