

# 西门子110KM变频器6SE6440-2UD41-1FB1

|      |                               |
|------|-------------------------------|
| 产品名称 | 西门子110KM变频器6SE6440-2UD41-1FB1 |
| 公司名称 | 上海鑫瑟电气设备有限公司                  |
| 价格   | .00/个                         |
| 规格参数 | 西门子:变频器                       |
| 公司地址 | 上海市松江区仓轩路211弄10号602           |
| 联系电话 | 18201996087                   |

## 产品详情

SIMATIC PDM Basic (包含 4 个 SIMATIC PDM 变量)

50 个 SIMATIC PDM 变量

? SIMATIC PDM Basic ???SIMATIC PDM Service ????? SIMATIC PDM ?????PDM Routing ?? PDM Integration in STEP 7/PCS 7 ???????? SIMATIC PDM ???????? 10?100 ? 1000 ??????????“????????”????????? SIMATIC PDM 1 Client ??????? 1 ????? SIMATIC PDM Server ??????????????????????

?????????????? PROFINET ? Ethernet ??? SIMATIC PDM ??????????????????

带有一个 PROFIBUS 子网的每个 S7 DSGW (数据记录网关) 有 10 个 SIMATIC PDM 变量

带有一个以上 PROFIBUS 子网的每个 S7 DSGW 有 20 个 SIMATIC PDM 变量

每个 IE/PB Link 有 10 个变量

每个现场设备 1 个变量 (特殊技术规格除外)

SIMATIC PDM ??????????V9.1

?? SIMATIC PDM Server ??? SIMATIC PDM  
????????????????SIMATIC PDM ????????????????????????????? SIMATIC PDM  
??

SIMATIC PDM Extended

SIMATIC PDM Server

2 x SIMATIC PDM 1 Client

# 100 个 SIMATIC PDM 变量

|              |                    |      |      |       |      |    |
|--------------|--------------------|------|------|-------|------|----|
| MM440-75/3   | 6SE6440-2UD17-5AA1 | 0.75 |      | 2     | 2.2  | A  |
| MM440-110/3  | 6SE6440-2UD21-1AA1 | 1.1  |      | 2.80  | 3.1  | A  |
| MM440-150/3  | 6SE6440-2UD21-5AA1 | 1.5  |      | 3.90  | 4.1  | A  |
| MM440-220/3  | 6SE6440-2UD22-2BA1 | 2.2  |      | 5.00  | 5.9  | B  |
| MM440-300/3  | 6SE6440-2UD23-0BA1 | 3    |      | 6.70  | 7.7  | B  |
| MM440-400/3  | 6SE6440-2UD24-0BA1 | 4    |      | 8.50  | 10.2 | B  |
| MM440-550/3  | 6SE6440-2UD25-5CA1 | 5.5  | 7.5  | 16.0  | 19   | C  |
| MM440-750/3  | 6SE6440-2UD27-5CA1 | 7.5  | 11   | 22.5  | 26   | C  |
| MM440-1100/3 | 6SE6440-2UD31-1CA1 | 11   | 15   | 30.5  | 32   | C  |
| MM440-1500/3 | 6SE6440-2UD31-5DB1 | 15   | 18.5 | 37.2  | 38   | D  |
| MM440-1850/3 | 6SE6440-2UD31-8DB1 | 18.5 | 22   | 43.3  | 45   | D  |
| MM440-2200/3 | 6SE6440-2UD32-2DB1 | 22   | 30   | 59.3  | 62   | D  |
| MM440-3000/3 | 6SE6440-2UD33-0EB1 | 30   | 37   | 71.7  | 75   | E  |
| MM440-3700/3 | 6SE6440-2UD33-7EB1 | 37   | 45   | 86.6  | 90   | E  |
| MM440-4500/3 | 6SE6440-2UD34-5FB1 | 45   | 55   | 130.6 | 110  | F  |
| MM440-5500/3 | 6SE6440-2UD35-5FB1 | 55   | 75   | 138.5 | 145  | F  |
| MM440-7500/3 | 6SE6440-2UD37-5FB1 | 75   | 90   | 168.5 | 178  | F  |
| MM440-9000/3 | 6SE6440-2UD38-8FB1 | 90   | 110  | 204.5 | 205  | FX |
| MM440-110K/3 | 6SE6440-2UD41-1FB1 | 110  | 132  | 244.5 | 250  | FX |
| MM440-132K/3 | 6SE6440-2UD41-3GB1 | 132  | 160  | 296.4 | 302  | GX |
| MM440-160K/3 | 6SE6440-2UD41-6GB1 | 160  | 200  | 354.0 | 370  | GX |
| MM440-200K/3 | 6SE6440-2UD42-0GB1 | 200  | 250  | 442.0 | 477  | GX |

??

## M54

??????????????? IP54

???? IP54 ??? IP54 ????????????? 400 mm??

???

顶部部件标准颜色为 RAL7035。如果需要让机柜具有某种特殊颜色，则顶部也可以喷涂这种颜色。而塑料模块（例如通风格窗）的颜色为 RAL 7035，不能漆成别的颜色。

对于带有滤芯的防护等级为 IP54 的型号，降额因子可能会偏离“一般技术数据”部分的表中提供的数据。根据要求，我们可提供相应的值。

???? IP54 ??????????????? (IP20)

