

各种规格海天注塑机料筒螺杆

产品名称	各种规格海天注塑机料筒螺杆
公司名称	舟山市福翔塑料机械制造有限公司
价格	.00/个
规格参数	品牌:福翔螺杆 型号:FX20105 规格:锁模力15T--25000T
公司地址	舟山市定海区金塘镇山潭东墩路2号
联系电话	86 0580 8591858 13905809167

产品详情

品牌	福翔螺杆	型号	FX20105
规格	锁模力15T--25000T	适用范围	海天注塑机

技术参数(technical specifications)调制硬度：hb260-290 (hardness of adjuster:hb260-290) 氮化硬度：hv800-1050(hardness of nitration: hv800-1050)氮化层深度：0.4~0.1mm(depth of nitrationcase:0.4~0.1mm)氮化脆度： 一级(fragility of nitration:less than grade 1)表面粗糙度：ra 0.4(roughness of the surface:ra 0.4)螺杆直线度：0.015mm(linearity of the screw:0.015mm)氮化后表面镀铬硬度： 900hv(the surface hard chromium plating hardness after nitrogenation 900hv)镀铬层厚度：0.5~0.10mm(chromium-plating layer thickness:0.05-0.10mm)双合金硬度：hrc56~65(hardness of double alloys:hrc56-65)双合金深度：0.8~2.0mm(depth of double alloys:0.8~2.0mm)材料工艺(materials and processes)优质38crmoaia(quality 38crmoaia)优质双相不锈钢(quality twin-phase stainless)优质粉末冶金材料(quality stellite powder surface spray)冷，热喷吐硬金属工艺(cold alloys hot alloys)先进渗碳工艺(advanced nitriding)耐腐蚀，耐磨双金属喷涂工艺(process of hot sprayed hard alloys)