

PA12 TR90 瑞士EMS 高抗冲 耐水解 抗紫外线 透明料

产品名称	PA12 TR90 瑞士EMS 高抗冲 耐水解 抗紫外线 透明料
公司名称	上海圆高塑化科技有限公司
价格	130.00/千克
规格参数	PA12:瑞士EMS TR90:PA12 瑞士EMS:TR90
公司地址	上海市青浦区练塘镇章练塘路588弄15号1幢2层4区113室
联系电话	15802190887

产品详情

Some of the values displayed above may have been converted from their original units and/or rounded in order to display the information in a consistent format. Users requiring more precise data for scientific or engineering calculations can click on the property value to see the original value as well as raw conversions to equivalent units. We advise that you only use the original value or one of its raw conversions in your calculations to minimize rounding error. We also ask that you refer to MatWeb's terms of use regarding this information. [Click here to view all the property values for this datasheet as they were originally entered into MatWeb.](#)

Users viewing this material also viewed the following:

EMS-Griltech Grilamid HP 1200 Nylon 12 Fiber (Staple Length = 43)

EMS-Griltech Grilamid HP 1200 Nylon 12 Fiber (Staple Length = 51)

EMS-Griltech Grilamid DN 80 Nylon 12 Monofilament

EMS-Griltech Grilamid HP 1200 Nylon 12 Fiber (Staple Length = 60)

Arkema Group Cristamid MS 1100 Semi-Aromatic Nylon (PASA) (Dry)

PA12 TR90 LXP 瑞士EMS

PA12 瑞士EMS TR-55

PA12 瑞士EMS TR55LX

PA12 瑞士EMS TR55LX-BLAU460

PA12 瑞士EMS TR-60

PA12 瑞士EMS TR-70

PA12 瑞士EMS TR-70LX

PA12 瑞士EMS TR-90

PA12 瑞士EMS TR90 BK

PA12 瑞士EMS TR90 BK9208

PA12 瑞士EMS TR90 GY9420

PA12 瑞士EMS TR90 LXP

PA12 瑞士EMS TR90 TL

PA12 瑞士EMS TR90 UV BLAU4149

PA12 瑞士EMS TR90-HELLBLAU

PA12 瑞士EMS TR90LS

PA12 瑞士EMS TR90LX

PA12 瑞士EMS TR90-WEISS

PA12 瑞士EMS TRV-4X9

PA12 瑞士EMS TRVX-50X9

PA12 瑞士EMS TRVX-50X9 BK 9230

PA12 瑞士EMS TRVX-50XP GREY L10394.3

PA12瑞士EMS TR90

PA12瑞士EMS TR70

PA12瑞士EMS RDJ2509.

PA12瑞士EMS L16W20

PA12瑞士EMS G21

PA12瑞士EMS TR55

PA12瑞士EMS TR55LX.

PA12瑞士EMS L20G.

PA12瑞士EMS LV-5H

PA12瑞士EMS LV-3H..

PA12瑞士EMS E47-S3. E55-S3

PA12 瑞士EMS XE3818

PA12 瑞士EMS XE3830

PA12 瑞士EMS TR-55

PA12 瑞士EMS TR55LX

PA12 瑞士EMS TR-90

PA12 瑞士EMS TR90-HELLBLAU

PA12 瑞士EMS TR90LX

PA12 瑞士EMS XS1332

PA12 瑞士EMS BM17

PA12 瑞士EMS FE7547 BK

PA12 瑞士EMS L20HL-BK

PA12 瑞士EMS L25 A NZ BK

PA12 TR90/瑞士EMS

Grilamid PA12 物性如需要完整物性联系我们

Physical PropertiesMetricEnglishComments

Density1.01 g/cc0.0365 lb/in

Filament Diameter400 m400 m

Mechanical PropertiesMetricEnglishComments

Elongation at Break25 - 45 %25 - 45 %

Tenacity0.297 - 0.396 N/tex3.37 - 4.49 g/denier

Thermal PropertiesMetricEnglishComments

Melting Point 178 ° C 352 ° F

Shrinkage 7.0 - 9.0 % 7.0 - 9.0 % Thermo Shrinkage, 180 ° C

Descriptive Properties

Heat Setting Medium-Set

规格级别 透明

???供应PA12,L20G挤出级注塑级瑞士EMS中粘未增强透明软尼龙；

????供应PA12,L25挤出级耐候耐磨耐冲瑞士EMS高粘未增强透明软尼龙；

????供应PA12,TR90,TR70,TR55注塑级瑞士EMS透明硬尼龙(透明眼镜料)；

????供应PA12,TR55LX挤出注塑级瑞士EMS黑色透明硬尼龙(墨镜)

????供应PA12,LV-2H , LV-3H,LV-5H瑞士EMS耐冲抗紫外线玻纤增强(20%,30%,50%)；

瑞士EMS : L20G , 2694 , AZM23 , CF7 , E62-S3 , ELY60 , FE5509 , FE5750 , FE8510 , G21 , GTR45 , L120
HL , LV-5H , TR-55 , TR55LX , TR-70 , TR-90 , XE3303 , XE3830 , XS1332 , BM17 , XE3877