八孔压砖机、八孔免烧粉煤灰砖机,质量好

产品名称	八孔压砖机、八孔免烧粉煤灰砖机,质量好	
公司名称	福建泉州永昌建材机械有限公司	
价格	.00/个	
规格参数	类型:砖头机械 成型周期:15-20(秒) 传动方式:电机振动为主,液压为辅	
公司地址	福建省泉州市南安市康美镇赤岭村	
联系电话	0595-86650578 13960276567	

产品详情

类型 传动方式 整机重量 外形尺寸	砖头机械 电机振动为主,液压为辅 8.5(t) 12600x2450x2500(mm)(c m)	振动频率	15-20(秒) 4000-4800(次/分) 60(hz) 60(kw)
主振形式 品牌 别名	电机振动为主 永昌 砖机、免烧砖机、多孔砖 机、压砖机、免烧砖机	总功率 型号 用途	28 KW (w) YC6-20A 可生产各种通体地砖、码 头连锁砖、植草砖、水利 砖、空心砌块、多孔砖、 免烧标砖等。

yc6-20a型全自动砌块成型机

一、主要技术参数:成型周期:15-20(秒)单料:3模/分钟双料(彩砖):2.5模/分钟

整机功率: 28 kw

机重量: 8 5 00kg激振力: 20kn托板规格: 860x680x20(mm)竹胶板外型尺寸: 12600x2450x2500(mm)

成型方式:台振——振动液压成型

注:以上产量表为理论计算值。成型周期、生产量与原材料、产品类型及其它因素有关。

三、主要技术特点:

1.控制系统:plc智能控制。人机界面,控制系统配置安全逻辑控制,生产程序及故障诊断显示功能,并有远程控制系统升级及故障诊断及排除功能,实现无需专业人士,只需简单培训即可掌握操作功能。2.振动器:采用变频电机多源式同步振动系统,频幅可调,实现低频加料,高频成型的工作原理,以适应不同材料及产品均可获得良好振实效果,振动加速度可达16个级。3.成型机架:采用高强型钢及特种焊接工艺制造,极其坚固。4.导向柱:采用超强特种钢材制成,表面镀铬具有良好的抗扭与耐磨能力。5.布料车布料:独特料车布料旋转强制下料装置,彻底解决湿浆及多孔布料难题。6.原材料:可充分使用沙、石粉、煤矸石、粉煤灰、钢渣等各种废渣。7.产品范围:可生产各种彩面(分层布料)及通体地砖、码头连锁砖、植草砖、水利砖、空心砌块、多孔砖、免烧标砖等。

1.

yc6-20a full-automatic carve the priece to model the machine

main technique characteristics:

1.control the system: the plc intelligence controls. man-machine interface, control the system to install the safe logic control, produce the procedure and breakdown to examine a patient to show the function, also the long range controls the system to get stripe and breaks down examine a patient and expel the function, carry out and didn"t need the professional, needing tobe trained in brief can immediately control to operate the function.

2.vibrate the machine: the adoption changes many source types of the electrical engineering to synchronously vibrate the system, the is adjustable, carrying out the low frequencyto add toanticipate, the high models of the work principle all can acquire by adapting the different material and product good flap the real results fruit, vibrating the accelerationcan amount to 16 classes.

3.model the machine:adopting a steel and special kind welds the craft manufacturing, very fastness.

4.lead to the pillar:adopting the super and strong special kind steel material makes into, the surface plates the chrome to have the good anti- to twist and bears the ability of whetting.

5.cloth car cloth:special anticipate the car cloth to revolve to compulsory descend to anticipate the device, thoroughly solve the wet syrup and many bore cloth hard nut to crackses.

6.at first material:can well use the sand, stone powder, coal gangue, powder ash from stove, the steel residue...etc.

various discard the residue.

7.product scope:can produce various a body a brick, wharf catena brick, plant the grass brick, water conservancybrick, hollow carve the piece, have another the bore brick and don"t need to burn to mark brick etc.

technical data:

cycle time: 15-20(s)

total power:23.2(kw)

total weight: 8000kg

exciting force:20kn

pallet pattem:860x680x20(mm)(bamboo gum plank)

shape size:12600x2450x2500(mm)

model the way:the set flaps vibrating the lipquid presses to model

control the way: the plc computer control full-automatic.

specification & capacity of main products:

itemssize(lxwxh)pcs./mouldpcs./hourpcs./8hour

hollow block390x190x19069827,856

porous bricks240x115x90152,45519,636

dimension bricks 240x115x53305,40043,200

dimension bricks 240x115x50325,76046,080

holland bricks200x100x60213,02424,192

note: the above yield form computes a value for the theories. modeling the period, volume of production has something to do with original material, product type and other factor.