

PP 台湾台化 K1023

产品名称	PP 台湾台化 K1023
公司名称	浙江昌宏塑胶原料有限公司
价格	.00/个
规格参数	品牌:台湾台化总代理 型号:K1023 产地:台湾
公司地址	义乌市江东街道端头二区58栋1号
联系电话	0579-15868975843 15868975843

产品详情

供应高流动、薄壁射出成型品PP原料

K1023 薄壁射出成型品、家庭用品、玩具、符合USP6級認證(例:針筒推桿) 通用級、流動性佳 物性表加工建議參數 SDS UL RoHS SVHC 環保證明 FDA.

本公司所生產之聚丙烯產品，均儲存於具有良好防護設備的倉庫，產品包裝完整，且儲存環境合宜(溫度<40 °C、濕度<80%)，其有效使用期限至少2年。唯客戶端之儲存環境未必都能符合此環境條件要求，因此建議客戶自購入聚丙烯膠粒產品後，6個月內應使用完畢。 The TAIRIPRO PP produced from FCFC are all stored in a warehouse with good protective equipment, packaging integrity, and appropriate storage environment (temperature <40 °C, humidity <80%), its shelf life for at least 2 years. However customer's storage environment conditions might not fully follow this requirement, it is recommended that customers from the acquisition of polypropylene pellets should be used within six months of completion.

台化 PP 樹脂射出/押出成形加工條件

項目 單聚物 Homo Polymer 隨意共聚物 Random Copolymer 耐衝擊共聚物 Impact Copolymer

規格

押出吹製級 扁紗級 薄膜級 射出級 纖維級 射出級 薄膜級 射出級 押出級

T1002

T1202

T2502

B1101

S1003

S1005

F2003AR

F2003AT

F2003AM

F2011

F1611

K1108

K1011

K1023

K1525

K1035

K2038

K2051

K2065

K1060

S1803

S1023

S1040

S2023

S2123

S2035

S1019

K4015

K4038

K4502

K4515

K4535

K4635

K4715

K4750

T3002

K4650

F4002

F4006

F4007

F4008

T4002

K7005

K7025

K8802

K8003

K8003AN

K8005

K8009

K8025

K8050

K8065

K9003

K9010

K9017

K3004

BC03ZX

K3009AN

K3009AU

KP03B

K3029

K7009AH

K7005AX

T7002

T8002

B8001

收縮率(%) 1.5~1.9 --- 1.4~1.8 --- 1.5~2.0 --- 1.4~1.8 1.4~1.8

螺桿溫度 () 200~230 200~270 220~260 200~290 220~260 220~240 190~220 180~230 200~230

射出壓力(kg/cm²) --- 80~120 --- 40~90 --- 30~60 ---

模溫 () 190~210 280~290 230~250 30~50 220~240 30~50 220~240 30~50 190~210

鑄模輪 /

冷卻輪水溫 () --- 30/50~60 30/30~40 --- 30/50~60 --- 30/30 --- /30~50

冷凍輪水溫 () --- 12~18 --- -