

REXROTH AZMB系列外齿轮高性能马达

产品名称	REXROTH AZMB系列外齿轮高性能马达
公司名称	南平市建阳区迪必达自动化科技有限公司
价格	.00/个
规格参数	-:- -:- -:-
公司地址	南平市建阳区区黄花山路45号大潭映像1幢3单元901室
联系电话	0599-8302509 13959199347

产品详情

Platform B

Fixed displacement

Size 2.5 ... 7.1

Continuous pressure up to 220 bar

Intermittent pressure up to 250 bar

FEATURES:

Consistent high quality based on large-volume production

Long service life

Wide speed range

Slide bearings for high loads

Optional reversible version for 2-quadrant and 4-quadrant operation

Numerous configuration variants available

Drive shafts according to ISO or SAE and customer-specific solutions

Line ports: connection flange or screw thread

High pressures though small installation space and low weight

Wide viscosity and temperature range

Technical data

TABLE OF VALUES

Size

2.53.144.556.37.1

Series

Series 3x

Displacement

V_g

cm

2.53.1544.556.37.1

Maximum continuous pressure

p₁

bar

220220220220220200

Maximum intermittent pressure

p₂

250250250250250250230

Minimum speed

at p₁

n_{min}

rpm

750750750750750750

Maximum speed

nmax

5000400040004000400035003500