

ME-8108台湾茂仁限位开关现货

产品名称	ME-8108台湾茂仁限位开关现货
公司名称	苏州亿稳盛机电有限公司
价格	80.00/只
规格参数	品牌:台湾茂仁 型号:ME-8108 产地:台湾
公司地址	苏州市相城区元和街道善济路158号峰汇商务广场4幢1127室（注册地址）
联系电话	15370037015

产品详情

小型横式限制開關 (Made in Taiwan)

功能：

可配合各種不同之連桿及頭

具多種使用特性曲線

接線頭具帽式覆蓋螺絲

可調式

內裝接地螺絲

防塵、防油、防水

適用溫度 +5 至 +160 . (-15 to +70) .

額定電壓：

5A 250V AC

0.4A 115 V DC

電氣迴路：

FIELD ADJUSTABLE：

Rotary motion roller lever and rod actuators are adjustable

through 360 ° . They may be set for operation clockwise, counter-clockwise, or in both directions. Operating heads may be positioned in any of four 90 ° positions.

EASY WIRING：

1. Loosen cover screws and remove cover.
2. Remove rubber strain relief from switch cover.
3. Slip strain relief over cable.
4. Fasten terminal screws and grounding screw tightly after inserting cables or terminals.
5. After wiring insert strain relief into the groove of the switch cover.
6. Fasten 3 cover screws evenly. Do not over tighten.
7. Recommended Cable-# 18/3 SJT Flexible.

特性：

Operating speed 0.5mm to 50m/sec

Operating frequency Mechanically:120 operations/min.

Electrcally:30 operatioms/min.

Contact resistance 15m max.(initial)

Insulation resistance 100M min,(at 500 VDC)

Dielectric strength 1,000VAC. 50/60 Hz for 1 minute between non-continuous terminals

2,000VAC. 50/60 Hz for 1 minute between each terminal and non-current carrying metal part and between each terminal and ground.

Vibration Malfunction durability:10 to 55 Hz;

1.5mm double amplitude.

Shock Mechanical durability:

Approx. 1,000m/sec² (approx.100G s)

Malfunction durability :

Approx.300m/sec² (approx.30G s)

Ambient temperature Operating : -15 to +70

Humidity 95% RH max

Service life Mechanically: 10,000,000 operations min

Electrically: 300,000 operations min,(2A,110VAC)MAX.

Degree of protection IEC 529 class IP65

ORDER GUIDE

標準型

ME-8104 ME-8107 ME-8018 ME-8111 ME-8112

ME-8122 ME-8166 ME-8169 ME-9101 ME-8000

金屬滾輪 (定製品)

ME-8104-M ME-8108-M

50mm 橡膠滾輪 (定製品) : 50mm

ME-8104-L ME-8108-L

塑膠滾輪 (定製品)

ME-8112-P ME-8122-P

動作柄1/4白鐵 3/4 彈簧(定製品)

ME-9101-HI

REMARK :

金屬滾輪型式 :

塑膠滾輪型式 :

50mm 橡膠滾輪型式 :

動作柄1/4白鐵 3/4 :

ME-9101-HI 1/4 steel and 3/4 spring

台湾茂仁限位开关：

ME-8107ME-8104ME-8111ME-8108ME-8112ME-8122ME-8166ME-8169ME-8000ME-9101ME-8107-MME-8104
-MME-8108-MME-8111-MME-8112-MME-8122-MME-8166-MME-8000-MME-8169-MME-9101-MME-8108-L
ME-8107-LME-8104-LME-8112-LME-8111-LME-8122-LME-8169-LME-8166-LME-8000-LME-9101-LME-8107-
PME-8104-PME-8108-PME-8111-PME-8166-PME-8122-PME-8112-PME-9101-PME-8000-P