

新款诚达防摔对讲机CD-Q8S配选赠送耳机/车充

产品名称	新款诚达防摔对讲机CD-Q8S配选赠送耳机/车充
公司名称	泉州诚达电子科技有限公司
价格	1200.00/台
规格参数	品牌:诚达 型号:CD-Q8S 类型:专业级
公司地址	中国 福建 南安市 南安市霞美电子工业区58号
联系电话	86 0595 86767495 13632339652

产品详情

品牌	诚达	型号	CD-Q8S
类型	专业级	类别	手持台
频率范围	136-174 , 400-480 , 350-390 (MHz)	射频输出功率	5 (W)
信道数	16 (个)	理论通讯距离	3-10 (km)
工作电压	7.4 (V)	频率稳定度	2.5 (ppm)
电池类型	锂电池	电池理论寿命	90 (h)
监听功能	有	外形尺寸	131.5X61.5X41.5 (mm)
重量	280 (g)	装箱数	50

诚达品牌防摔对讲机cd-q8s特点简介

reaches the brand against to fall the intercom cd-q8s characteristic synopsis honestly

赠送品2选1 charge of 1 2 chosen

赠送品2选1 charge of 1 2 chosen

详细说明detailed :

1、监听功能the monitoring function

可监听到当前信道的微弱声音,该功能有助于收听到微弱信号

may monitor the current channel's weak sound, this function is helpful in listens to the weak signal

2、信道扫描channel 2 and scanning

按下扫描键,对信道逐个扫描,可接收到所有信道的通话

presses down scans the key, scans one by one to the channel, may receive all channel's telephone conversation

3、声控功能vox/ function vox

开启声控功能时,无需按ptt键便可进行通话

when opening voice control function, does not need to press the ptt key then to be possible to carry on the telephone conversation

4、电脑写频writes frequent computer

通过电脑写频软件对功能参数进行设置 软件为kpg-87d

writes the frequency software through the computer to carry on to the function parameter establishes the software is kpg-87d

5、静噪等级设置 (0~9级) static chirp rank establishment (0~9 levels)

9级静噪,根据不同环境选择您所需要的静噪等级,降低背景噪音

9 levels static chirp, chooses the static chirp rank which according to the different environment you need, reduces the background noise

6、发射超时定时器tot /launch overtime timer tot

防止对讲机过久占用某个信道,避免不慎占用信道的现象

prevents the intercom to be excessively long takes some channel, avoids taking channel's phenomenon carelessly

7、宽/窄带转换a thin strip conversion

通过写频软件可设置每个信道间隔为25khz或12.5khz

through writes the frequency software to be possible to establish each channel spacing is 25khz or 12.5khz

8、低电提醒lower electricity remind

电池电量不足时提醒您更换电池

when battery capacity insufficiency reminds you to replace the battery

9、繁忙信道锁定busy channel locking

防止用户接收未经许可的信号及向繁忙信道发送信号，保持信道整洁和免受干扰

prevents the user receive without the permission signal and to the busy channel sending signal, maintains the channel neat and is exempt from the disturbance

10、自动省电功能automatically save electricity function

未接收到信号或无操作时，对讲机将自动进入省电模式，降低耗电量，从而延长电池的使用时间

when has not received the signal or the no-operation, the intercom will enter the province electricity pattern automatically, reduces the power consumption, thus lengthens battery"s period of revolution

11、ctcss/ cdcss及尾音消除ctcss/cdcss and the end tone eliminate

具有38组标准亚音频和83组标准亚音数码,支持非标准ctcss/cdcss,设置ctcss或cdcscs后,可以消除同频所带来的干扰,还可以消除发送方由于通话结束、载波引起的“咔嚓”声

has 38 groups of standard subaudio frequencies and 83 group of standard asia sound numerical code, supports non-standard ctcss/cdcscs, after establishing ctcss or cdcscs, may eliminate the disturbance which the frequency brings, but may also eliminate the transmitting end, because talked over the telephone finishes, the carrier to cause “ carbazole ” the sound

12、收音机功能fm radio function

13、支持非标亚音频support non-standard the audio

14、发射功率为：实5w/the emissive power is: solid 5w

15、频率范围frequency：136-174mhz；350-390mhz；400-480mhz；

16、长时间待机/高容量电池组：电池容量2000毫安

the long time waits for an opportunity/the high-capacity battery: lithium battery capacity 2000 milliamperes

17、可选配赠送车充/耳机may choose and match the present vehicle sufficient/earphone

18、外观设计以防摔，防雨水土尘保护为主，是各种工程，酒店，保安，物业等场地使用对讲机首选。

the outward appearance design by against falls, the rainproof water and soil dust protection primarily, is each kind of project, the hotel, the security, location use intercom first choices and so on property.

原出厂配置一电一充一耳机/车充有：

机身1个，电池一个，充电器1个，天线1支，诚达cd-22k耳机/12v车充1个（赠品2选一），说明书1本，包装盒1套。

original leaving the plant disposes electricity sufficient earphone/che chongyou:

fuselage 1, battery, battery charger 1, antenna 1, reaches cd-22k the earphone /12v vehicle sufficient 1（complimentary gift 2 to elect honestly one），instruction booklet 1 book, packing box 1 set.

整体规格overall specifications	
频率范围frequency	136-174mhz ; 350-390mhz ; 400-480mhz ;
工作电压working voltage	7 . 4v
频率稳定度rate stability	± 2.5ppm
信道数channel number	16
频率步进frequency step	25khz
工作温度范围work temperature range	-30 +50
电池使用时间battery time	90小时
重量weight	280克
产品尺寸sizes	131.5mm × 61.5mm × 41.5mm
通信距离communication gap	3-10km
抗防摔度resistance to prevent and degrees	93 %
天线阻抗antenna impedance	50欧姆 , 加感天线
接地方法grounding method	负极
接收部分receive part	
灵敏度sensitivity	0.16uv
信噪比her letter than	-45db
音频功率audio power	300mw
邻信道功率other channels power	65db
杂散抑制away by inflation	-65db
互调抗干扰to tune each antigen	50db
音频响应audio response	+1 ~ -3db
发射部分launch part	
发射功率launch power	5w
剩余调频the rest of the fm	45db
杂散抑制away by inflation	65db
最大偏频the frequency of the largest	5khz
音频失真audio distortion	1.5 %
调制方式modulation way	computer fm

详细说明detailed :

1、 监听功能the monitoring function

可监听到当前信道的微弱声音,该功能有助于收听到微弱信号

may monitor the current channel"s weak sound, this function is helpful in listens to the weak signal

2、 信道扫描channel 2 and scanning

按下扫描键,对信道逐个扫描,可接收到所有信道的通话

presses down scans the key, scans one by one to the channel, may receive all channel"s telephone conversation

3、声控功能vox/ function vox

开启声控功能时,无需按ptt键便可进行通话

when opening voice control function, does not need to press the ptt key then to be possible to carry on the telephone conversation

4、电脑写频writes frequent computer

通过电脑写频软件对功能参数进行设置 软件为kpg-87d

writes the frequency software through the computer to carry on to the function parameter establishes the software is kpg-87d

5、静噪等级设置 (0~9级) static chirp rank establishment (0~9 levels)

9级静噪,根据不同环境选择您所需要的静噪等级,降低背景噪音

9 levels static chirp, chooses the static chirp rank which according to the different environment you need, reduces the background noise

6、发射超时定时器tot /launch overtime timer tot

防止对讲机过久占用某个信道,避免不慎占用信道的现象

prevents the intercom to be excessively long takes some channel, avoids taking channel"s phenomenon carelessly

7、宽/窄带转换a thin strip conversion

通过写频软件可设置每个信道间隔为25khz或12.5khz

through writes the frequency software to be possible to establish each channel spacing is 25khz or 12.5khz

8、低电提醒lower electricity remind

电池电量不足时提醒您更换电池

when battery capacity insufficiency reminds you to replace the battery

9、繁忙信道锁定busy channel locking

防止用户接收未经许可的信号及向繁忙信道发送信号，保持信道整洁和免受干扰

prevents the user receive without the permission signal and to the busy channel sending signal, maintains the channel neat and is exempt from the disturbance

10、自动省电功能automatically save electricity function

未接收到信号或无操作时，对讲机将自动进入省电模式，降低耗电量，从而延长电池的使用时间

when has not received the signal or the no-operation, the intercom will enter the province electricity pattern automatically, reduces the power consumption, thus lengthens battery"s period of revolution

11、ctcss/ cdcss及尾音消除ctcss/cdcss and the end tone eliminate

具有38组标准亚音频和83组标准亚音数码,支持非标准ctcss/cdcss,设置ctcss或cdcscs后,可以消除同频所带来的干扰,还可以消除发送方由于通话结束、载波引起的“咔嚓”声

has 38 groups of standard subaudio frequencies and 83 group of standard asia sound numerical code, supports non-standard ctcss/cdcscs, after establishing ctcss or cdcscs, may eliminate the disturbance which the frequency brings, but may also eliminate the transmitting end, because talked over the telephone finishes, the carrier to cause “ carbazole ” the sound

12、收音机功能fm radio function

13、支持非标亚音频support non-standard the audio

14、发射功率为：实5w/the emissive power is: solid 5w

15、频率范围frequency：136-174mhz；350-390mhz；400-480mhz；

16、长时间待机/高容量电池组：电池容量2000毫安

the long time waits for an opportunity/the high-capacity battery: lithium battery capacity 2000 milliamperes

17、可选配赠送车充/耳机may choose and match the present vehicle sufficient/earphone

18、外观设计以防摔，防雨水土尘保护为主，是各种工程，酒店，保安，物业等场地使用对讲机首选。

the outward appearance design by against falls, the rainproof water and soil dust protection primarily, is each kind of project, the hotel, the security, location use intercom first choices and so on property.

原出厂配置一电一充一耳机/车充有：

机身1个，电池一个，充电器1个，天线1支，诚达cd-22k耳机/12v车充1个（赠品2选一），说明书1本，包装盒1套。

original leaving the plant disposes electricity sufficient earphone/che chongyou:

fuselage 1, battery, battery charger 1, antenna 1, reaches cd-22k the earphone /12v vehicle sufficient 1（complimentary gift 2 to elect honestly one），instruction booklet 1 book, packing box 1 set.

整体规格overall specifications	
频率范围frequency	136-174mhz；350-390mhz；400-480mhz；
工作电压working voltage	7 . 4v
频率稳定度rate stability	± 2.5ppm
信道数channel number	16
频率步进frequency step	25khz
工作温度范围work temperature range	-30 +50
电池使用时间battery time	90小时
重量weight	280克
产品尺寸sizes	131.5mm × 61.5mm × 41.5mm
通信距离communication gap	3-10km
抗防摔度resistance to prevent and degrees	93 %
天线阻抗antenna impedance	50欧姆，加感天线
接地方法grounding method	负极
接收部分receive part	
灵敏度sensitivity	0.16uv
信噪比her letter than	-45db
音频功率audio power	300mw
邻信道功率other channels power	65db

杂散抑制away by inflation	-65db
互调抗干扰to tune each antigen	50db
音频响应audio response	+1 ~ -3db
发射部分launch part	
发射功率launch power	5w
剩余调频the rest of the fm	45db
杂散抑制away by inflation	65db
最大偏频the frequency of the largest	5khz
音频失真audio distortion	1.5 %
调制方式modulation way	computer fm