

中兴ZXDU68S601通信开关电源柜

产品名称	中兴ZXDU68S601通信开关电源柜
公司名称	山东格伦德电源科技有限公司
价格	3000.00/台
规格参数	
公司地址	山东济南市历城区山大北路
联系电话	15315678277

产品详情

中兴ZXDU68S601通信开关电源柜

室内通信开关电源柜基本介绍

1、ZXDU68 T601电源柜介绍

ZXDU68 T601中兴电源系统块采用当代先进的电源技术和工艺，XDU68 T601专门为各类计算机网络、电力、石油等行业而设计。XDU68 T601具有高效、高功率密度、高可靠性、智能化控制和造型美观等特点。XDU68 T601输出电流600A，输出电压：-48V，功率34800W。

2、中兴ZXDU68 T601通信电源系统特点

室内型直流电源系统，额定直流输出电压为-53.5V。

满配置12个ZXD2400整流器，系统输出功率为34800W。

采用三相交流输入，宽输入电压范围（相电压80V ~ 300V）。

蓄电池外置在ZXDU68 T601系统机柜外。ZXDU68 T601系统机柜内集交流配电、直流配电、整流和监控于一体。

整流器及监控单元支持热插拔。

具有完善的监控管理功能

节能管理：支持自动节能、暂时非节能、非节能。

蓄电池管理：支持温度补偿、充电限电流、自动周期均充、自动周期测试。

下电管理：支持自动二次下电保护，支持手动下电控制。

信息管理：支持系统信息查询、告警信息查询、历史记录查询。

告警提示：支持声音告警、光告警、干接点告警和通讯告警。

支持RS232、RS485、干接点、IP等多种监控组网方式。

3、技术指标

适用环境

工作温度：-5 ~ +45 ， +15 ~ +25

存储温度：-40 ~ +70

相对湿度：10% ~ 90%（无冷凝），40% ~ 60%

大气压：70 kPa ~ 106 kPa

交流配电

交流输入制式三相五线制（L1/L2/L3/N/PE）

额定交流输入电压相电压：220 V，线电压：380 V

交流输入电压范围可波动范围（相电压）：80 V ~ 300 V

, zte ZXDU68S601 communication switching power supply cabinet interior communication switching power supply cabinet basic introduction 1, ZXDU68 T601 power ark ZXDU68 T601 zhongxing power system using the power of the modern advanced technology and craft, XDU68 T601 specially for all types of computer network, electric power, oil and other industries. XDU68 T601 has high efficiency, high power density, high reliability, intelligent control and elegant, etc. XDU68 T601 output current 600 a, output voltage: - 48 v, power 34800 w. 2, zte ZXDU68 T601 features indoor type dc power supply system, communication power supply rated dc output voltage of 53.5 V. 12 ZXD2400 rectifier with configuration, the system output power is 34800 W. Based on three-phase ac input, wide input voltage range (phase voltage 80 V ~ 300 V). External battery outside ZXDU68 T601 system cabinet. ZXDU68 T601 ac power distribution, dc power distribution system inside the cabinet set, rectifier and monitoring. Support hot-swappable rectifier and monitoring unit. Has the perfect monitoring management function and energy saving management: support automatic energy-saving, temporarily not energy-saving, permanent not energy-saving. Battery management: support for temperature compensation, charge limited current, automatic cycle are filling, automatic cycle test. The electricity management: support automatic secondary electrical protection, under the support manual electric control. Information management: support system information query, the alarm information query, history inquiry. Warning: support the sound alarm, light alarm, and the dry contacts alarm and communication alarm. Support RS232, RS485, dry contact, IP monitoring network a variety of ways. 3, technical indicators applicable environment working temperature: - 5 ~ + 45 , 15 ~ + + 25 storage temperature: - 40 ~ + 70 relative humidity: 10% ~ 90% (without condensate), 40% ~ 60%, atmospheric pressure 70 kPa to 106 kPa ac distribution ac input formats three-

phase five wire (L1 / L2 / L3 / N/PE) rated ac input voltage phase voltage: 220 V, line voltage: 380 V ac input voltage range can range (phase voltage) : 80 V to 300 V