

退火镀锡机 ZL 退火镀锡机

| | |
|------|--|
| 产品名称 | 退火镀锡机 ZL 退火镀锡机 |
| 公司名称 | 张家港市兆隆机电有限公司 |
| 价格 | .00/个 |
| 规格参数 | 品牌:ZL 型号:ZL-40H 用途:退火镀锡机 |
| 公司地址 | 中国 江苏 张家港市 乐余镇镇北路乐西工业区 |
| 联系电话 | 86 0512 58960286/58962836 013901928475 |

产品详情

| | | | |
|----|-------|----|--------|
| 品牌 | ZL | 型号 | ZL-40H |
| 用途 | 退火镀锡机 | 别名 | 铜线退火 |

退火炉内炉膛设计炉温分部均匀，节能效果良好；

双锡炉设计，产品可多样化同时生产；

双层式卷取机设计，节省设备使用面积；

zl-40h

continuous annealing tin. coating machine

add one room inside the annealer , can make the temperature impartial distribution..

dual tinning tank design , it can produce two kind of tin-coating copper wire in the same time.

spooler arranged in double layer can save space.

continuous annealing tin-coating machine

| | | |
|---------------------|--------------|--------------|
| machine type | zl-24h | zl-32h |
| no. of wire | 24 | 32 |
| wire dia. | 0.10-0.32mm | 0.10-0.32mm |
| line speed | max 300m/min | max 300m/min |
| pay-off bobbin size | max 300- 400 | max 300- 400 |
| spooler dia. | pt5-pt25 | pt5-pt25 |

| | | |
|-------------------------|--|-----------------|
| heater consumption | 53kw | 62.4kw |
| power consumption | 7.5kw | 10kw |
| total power consumption | 60.5kw | 72.4kw |
| machine dimension | 18300*2200*1500 | 18800*2200*1600 |
| annealer | continuous annealing by heater | |
| take-up type | single spooler drive by torque motor | |
| usage | tin-coating the round copper wire or by tension wire | |
| pay-off stand | by tension wire | |
| tin-coating type | dual tinning tank arrange in horizontal type | |