

粗选机 纸源 粗选

产品名称	粗选机 纸源 粗选
公司名称	诸城市旭日东机械有限责任公司
价格	39000.00/台
规格参数	品牌:纸源 型号:1-5m 用途:粗选
公司地址	中国 山东 诸城市 隆源路(海关南200米)
联系电话	86 0536 6081238 13963611988

产品详情

品牌	纸源	型号	1-5m
用途	粗选	别名	粗选筛、杂质分离机

一、概述

xcx系列粗选机是用于制浆造纸行业废纸处理流程，处理经高浓碎解后的浆料，收集并浓缩浆料中的杂质，以减轻后道工序中筛选和净化设备的负担。与高浓碎浆机配套使用，可缩短处理周期，避免杂质细化，提高碎解系统的生产能力。

该系列产品在高浓碎浆机之后，经高浓碎浆机碎解的浆料经过稀释后，在落差作用下进入机体内，由于泵的抽吸作用，浆料通过筛板进入良浆室，经出浆口排出；轻杂质在水压作用下送入圆筒筛处理，回收水和纤维，排出重渣。转子高速旋转起到清洗筛板的作用，以免筛孔堵塞；转子的特殊结构，避免了杂物的细化。

三、整机结构

本机主要由壳体、转子装置、底座、传动部分等组成。

壳体由钢板焊接而成，其端部焊有进浆口及重渣排出口，前部焊有轻渣出口，壳体两侧有底脚及底座相连。

本机主要由转子、主轴、出浆盘、筛板装置、轴承座、传动支架、大皮带轮等组成。转子为耐磨铸钢材料；筛板为不锈钢材料。

底座由钢板与槽钢焊成，用于支撑壳体及传动装置。

传动部分主要由电机、小皮带轮、电机支架及三角带组成。

first, an overview of xcx series rough sorting machine is used to deal with waste paper pulp and paper industry processes, handle broken by the high concentration of the slurry after the solution, collected and concentrated slurry of impurities, so as to reduce the procedures after the screening and purification equipment in the burden of . high consistency pulper with machine use, can shorten the treatment cycle, to avoid impurities in refined broken solutions enhance the productive capacity of the system.this series of products in high concentration after the pulper, the pulper high concentration of the slurry after breaking solution diluted in the gap between the role of the body into the machine, due to the suction pump effect, slurry through the sieve into the pulp chamber liang by a plasma discharge mouth; light impurities in the hydraulic cylinder into the sieve under treatment, recycling of water and fiber, re-emit java. high-speed rotation of rotor plate to play the role of cleaning in order to avoid plugging sieve; rotor special structure, the refinement to avoid debris.second, the main specifications and technical parametersmodel xcx0.8 xcx 1.2 xcx 2 xcx 2.5 xcx 3nominal volume: m³ 0.8 1.2 2 2.5 3rotor speed: r / min 600 470 430 370 310treatment concentration:% 4-5production capacity: t / d 20-30 35-45 60-80 70-100 90-120sieve size: mm 6- 12use dynamic allocation: kw 22 30 45 75 90three machine structuremainly by the local shell, rotor installation, base, transmission and other parts of the composition.shell welded together from steel plate, and its tip into the solder paste has the mouth and re-exports of slag pai, the former department of welding slag have light exports, both sides of the bottom shell and the base connected to the foot.this machine mainly by the rotor, the main axis of the plasma disk, plate device, bearing seat, drive frame, composed of large pulley. rotor for wear-resistant cast steel material; plate for stainless steel materials.base from steel plate and welded into a channel for supporting the shell and gear.drive by some of the main motor, a small pulley, the electrical component stent and triangle.