K100系列(增量式)旋转编码器

产品名称	K100系列(增量式)旋转编码器
公司名称	上海恒祥光学电子有限公司
价格	700.00/件
规格参数	恒祥:上海 K100:外径Φ100mm,厚度为 上海:松江
公司地址	上海市徐汇区龙吴路1594号（划船俱乐部内）
联系电话	86-02154613487 18930077369

产品详情

K100系列(增量式)旋转编码器

增量式(通用型,空心轴,抱扣形式)

外形尺寸：体积小,外径Φ100mm,厚度为50mm

轴　径：Φ45mm贯穿(其它轴径可选Φ30mm;Φ32mm;Φ35mm;Φ38mm;Φ40mm;Φ42mm)

连接方式：9芯电脑专用插座侧出

输出形式：集电极开路、电压、互补和差分输出（长线驱动26LS31）

分 辨 率：可达5000P/R

电源电压：可选①DC5V；②DC8V-24V

防护等级：IP50

外罩质地：铝

重 量：约697g (包装状态)

K100 series (incremental type) Rotary encoder

Incremental type (general type,hollow shaft, clasp buckle style)

External dimensions : Small volume, external diameter : Φ100mm, thickness : 48mm

shaft diameter : Φ45mm (hollow) (other optional : Φ30mm; Φ32mm; Φ35mm; Φ38mm; Φ40mm; Φ42mm)

Outlet type : 9 cores socket that only for computer on the side

Output mode : Collector open circuit output , voltage output , complementary output and difference output (long wire drive 26LS31)

Resolution : up to 5000P/R

Supply voltage : Optional : DC5V,DC8V-24V

Protection grade : IP50

Crust : aluminum

Weight : about 697g (with package)