

1
2
0
0

载荷中心/load centre c mm 600

到顶限重/max load at top kg 1000

1
0
0
0
/
8
0
0
/
6
0
0

门架起升高度系列/lifting height h mm 1600

2
5
0
0
/
2
9
0
0
/
3
3
0
0

下降后货叉距地高度/lower height h	mm	90
转弯半径/turning tadius r	mm	1315
车身总长/overall length l	mm	1725
车身总宽/overall width b	mm	830
车身静止高度/min height h2	mm	1975

1
8
5
0
/
2
0
5
0
/
2
2
5
0

门架起升后高度/max height h1	mm	1975
-----------------------	----	------

3
1
2
0

标准货叉尺寸(长/宽/高)/standard fork(l/w/h)	mm	1150 × 160 × 70
货叉外宽/fork overall size b1	mm	560
货叉内宽/fork inside size b2	mm	240
提升速度(满载/空载)/lifting speed(with/withoutload)	mm/s	80/130
下降速度(满载/空载)/lowering speed(with/withoutload)	mm/s	110/90
制动方式/type of driver		脚刹制动/manual
承载轮/load wheel	mm	80 × 70(尼龙/nylon)

平衡轮/balance wheel mm 180 × 50(尼龙/nylon)

提升电机/lifting motor kw 1.6

蓄电池(电压/容量)battery(voltage v/ah
/capacity) 12v120ah

自重(含电池)/weight(with
battery) kg 400

4
7
0
/
4
9
0
/
5
2
0