

德立功YFZ02-D医用针针尖强度、刺穿力测试仪

产品名称	德立功YFZ02-D医用针针尖强度、刺穿力测试仪
公司名称	昆山德立功自动化设备有限公司
价格	.00/个
规格参数	品牌:德立功
公司地址	昆山市花桥镇立德企业家园区1号楼1室（注册地址）
联系电话	18511156696

产品详情

YFZ02-D医用针针尖强度、刺穿力测试仪

Medical Needle Tip Strength and Puncture Force Tester

采用5.7英寸（120×90）PLC多彩液晶显示屏，中文菜单操作。公称规格、测试项目、应加载荷、打印、测试、上行、下行、时间、标定。由键盘控制液晶显示屏上的菜单，机载打印测试数据。

YFZ02-D医用针针尖强度、刺穿力测试仪完全符合“YY0043-2016”《医用缝合针》的标准设计制造。

测试项目：强度、刺穿力；

公称规格：0.2～1.8mm；

设定荷载：0.2～2.0N，

精度：±1%；

加载速率：加载到设定值时其速度 10mm/s

钢块硬度HRC 60

打印方式：每次可打印3次刺穿力测试数据及平均值和强度测试结果。

净重：11kg 外形尺寸：400×290×260（mm）

部分清单：

1.主机一台 2.打印纸1卷3.夹具一套4.砝码一套5.质保一年

6.操作说明7.仪器终身免费依国家标准规定升级服务

Using 5.7 inch (120 *90) PLC multi-color LCD display, Chinese menu operation. Nominal specifications, test items, payload, printing, testing, upstream, downstream, time and calibration.

The menu on LCD screen is controlled by keyboard, and the test data is printed on board. YFZ02-D Medical Needle Tip Strength and Puncture Force Tester fully conforms to the standard design and manufacture of "YY0043-2016" Medical Suture Needle.

Test items: strength, penetration force;

Nominal specification: 0.2-1.8mm;

Setting load: 0.2-2.0N,

Accuracy: +1%;

Loading Rate: When loaded to a set value, its speed is less than 10 mm/s

Hardness of steel block HRC (> 60)

Printing method: 3 times of test data of penetration force, average value and strength test results can be printed each time.

Net weight: 11kg shape size: 400 x 290 x 260 (mm)

Part of the list:

1. A mainframe 2. Printing paper 1 roll 3. Fixture set 4.

Weight set 5. Quality guarantee for one year

6. Operational instructions 7. Free upgrade service of

instrument in accordance with national standards for life