

# 插拔管专业型电子镇流器QT-T/E

产品名称	插拔管专业型电子镇流器QT-T/E
公司名称	南京奇正照明有限公司
价格	.00/个
规格参数	功率:70 ( W ) 类型:电子镇流器 电压:230-240 ( V )
公司地址	中国 江苏 南京市玄武区 南京市珠江路88号新世界中心B座4210室(公司邮箱:xzliu@lamp
联系电话	86 025 84703603 13914713497

## 产品详情

功率	70 ( W )	类型	电子镇流器
电压	230-240 ( V )		
应用			
dimnable		是	
type of protection		ip20	
lamp start		warm start	

### 综合描述

design / version	ecg standard
standards	根据 din vde 0875/cispr 15/en 55015标准   根据 en 61547标准   根据 en 61000-3-2 标准
energy label - eei	a2
sstl-number	4031140

### 技术方面 - 电参数

operating frequency	40 ... 95 khz
mains frequency	50-60 hz
lamp wattage	70 w
power factor c	0.98
nominal voltage	230-240 v

dc voltage	176...254 v <sup>2)</sup>
max. no. of ecgs on circuit breaker 10a	17
max. no. of ecgs on circuit breaker 16a	28

### 技术方面 - 形状

mounting hole spacing, length	129.5 mm
width	79 mm
height	33 mm
length	123 mm

### 技术方面 - 温度

max. casing temp. in case of fault	110 ° c
max. operating temp. at the tc point	65 ° c
ambient temperature range	-10 ... +50 ° c
storage temperature	-40 ... 85 ° c
relative humidity	5 ... 85 % <sup>3)</sup>

### 包装种类举例

ear4 (包装个) 0792002	单位尺寸规格 (mm)	箱内装 (只)	毛重 (g)	体积 (立方分米)
4050300792019	210,000 mm x 80,000 mm x 250,000 mm	箱(内装12 只)	2.380,000 克 (0,000 克)	4,200 立方分米

### 系统总览

operatio n of ecg with	length in mm	number of lighting outlet	length in mm	width in mm	height in mm	system power c onsump tion in w (ecg)	system power c onsump tion in w (ccg)	system power c onsump tion in w (llb)	lumino us flux with ecg in lumen	lumino us flux in lumen (ccg)	power factor
dulux t/e 70	235 mm	1	123 mm	79 mm	33 mm	77 w			5200 lm		1

battery voltage may drop to 176v. lamps must be ignited at over 198v however. same luminous flux with direct current and alternatingcurrent amalgam lamps such as dulux t/e in (red stamp) are not suitable for outdoor lighting (ta<5 ° c) or in most emergency lighting applications where a fast run-up is necessary ignition must take place above 198 v.

max. 56 d/y at 85%

