T5专业型电子镇流器QT-FH 4X14 CW

产品名称	T5专业型电子镇流器QT-FH 4X14 CW
公司名称	南京奇正照明有限公司
价格	.00/个
规格参数	功率:14（W） 类型:电子镇流器 电压:230-240（V）
公司地址	中国 江苏 南京市玄武区 南京市珠江路88号新世界中心B座4210室(公司邮箱:xzliu@lamp
联系电话	86 025 84703603 13914713497

产品详情

功率	14（W）	类型	电子镇流器
电压	230-240（V）		

应用

dimmable	是
type of protection	ip20
lamp start	warm start

综合描述

design / version	ecg standard
seg no.	7980051
standards	根据 din vde 0875/cispr 15/en 55015标准 | 根据 en 61547标准 | 根据 iec 61000-3-2/en 61000-3-2标准
energy label - eei	a2
sstl-number	4031074

技术方面－电参数

operating frequency	≈ 30 khz
mains frequency	50-60 hz
th full width at half maximum	230 μs
lamp wattage	4 * 14 w

power factor c	0.96
nominal voltage	230-240 v
dc voltage	176...254 v
ip inrush current	20 a
max. no. of ecgs on circuit breaker 10a	17
max. no. of ecgs on circuit breaker 16a	28

技术方面－形状

mounting hole spacing, length	415 mm
width	42 mm
height	30 mm
wire preparation length, output side	8.5 ... 9.5 mm
wire preparation length, input side	8.5 ... 9.5 mm
length	423 mm

技术方面－光参数

luminous flux	4 * 1350 lm

技术方面－温度

max. casing temp. in case of fault	110 ° c
max. operating temp. at the tc point	70 ° c
ambient temperature range	-20 ... +50 ° c
storage temperature	-40 ... 85 ° c
relative humidity	5 ... 85 %2)

包装种类举例

ean 4050300459097	包装个/单位尺寸规格装(内装1只); 毛重	44,000 mm x 29,000 mm x 424,000 mm	399,000 克 (0,000 克)	0,541 立方分米
4050300459103	箱(内装20 只)	250,000 mm x 158,000 mm x 437,000 mm	8.135,000 克 (0,000 克)	17,262 立方分米

系统总览

operation of ecg with	length in mm	number of lighting outlet	length in mm	width in mm	height in mm	system power consumption in w (ecg)	system power consumption in w (ccg)	system power consumption in w (llb)	luminous flux with ecg in lumen	luminous flux in lumen (ccg)	power factor
he 14	549 mm	4	425 mm	39 mm	30 mm	65 w			4 * 1200 lm		