

中规、美规、欧规插墙式USB电源适配器充电器

产品名称	中规、美规、欧规插墙式USB电源适配器充电器
公司名称	上海雍慧电子技术有限公司
价格	.00/个
规格参数	品牌:雍慧 型号:5W-12W 适用产品:数码相机
公司地址	上海市金山区海丰路65号1320室
联系电话	021-54356753

产品详情

品牌	雍慧	型号	5W-12W
适用产品	数码相机	输入电压范围	80-264VAC
输出电压	5V	OEM	可OEM

5w series

universal input a dapter switching power supply

features

*meet ceclow power consumption

*class b emi < 250ua leakage

applications

*computer*communication*consumer

safety approvals(60950)

*ccc*gs*ul

output specifications

x=represents the input voltage range 4.5-8.1v

y=us/eu/uk/au/ka/ch...(us means us-plug used,eu means eu-plug used,ukmeans...)

ccc=3 digit number which represents the output voltage

ddd=3 digit number which represents the output current

model	input voltage		output			
	range	frequency	vdc	reg.	a(max)	w(
dsc-5wu-05 xyccc ddd	200-240v	50/60hz0.2a	4.5-8.1v	± 15%	1.0	5.0
dsc-5wu-05xyccc ddd	100-240v	50/60hz0.2a	4.5-8.1v	± 18%	1.0	5.0

dsc-5wu characteristics

ac input voltageoperation temperature

90 to 264 vac0 to 40

ac input frequency:storage temperature

47 to 63 hz-20 to +60

ac input current(full load)mtbf

0.2arms(120vac)50000-100000 by option

0.2arms(240vac)(80%max load,nominal voltage,25)

leakage currentemissions

less than 250 μ a,(nominal voltage)fcc class b

dielectric withstand(hi-pot)en 55022 b

3000vac,1 min,10ma

hold-up time(full load)immunity

5ms 120vac61000-4-2,level 3

5ms 240vac61000-4-3,level 2

over current protection61000-4-4,level 2

short circuit,auto restart61000-4-5,level 3

61000-4-6,level 2

61000-4-11