

雕刻机/木工雕刻机 力博

产品名称	雕刻机/木工雕刻机 力博
公司名称	南京智拓电子经营部
价格	24800.00/台
规格参数	是否提供加工定制:是 品牌:力博 型号:LB-1212
公司地址	中国 江苏 南京市栖霞区 樊甸100号
联系电话	086 025 83682910/83683678 18602559704

产品详情

是否提供加工定制	是	品牌	力博
型号	LB-1212	电源电压	220V
额定功率	2200 (W)	铣刀直径	3.175/4/6 (mm)
主轴钻速	0-24000 (r/min)		

性能特点:

- 2 机身采用厚壁钢管焊接，经巨型龙门刨处理，确保机床精度高，钢性强
- 2 整机采用进口高精度滚珠丝杆、导轨，运动平稳，精度更高
- 2 三轴均采用全防尘结构，确保机器使用寿命长久
- 2 机电全优设计，精选各种电气配件，将故障率降到最低
- 2 具有断点记忆、断电续雕加工时间预测等功能，保证在意外情况下加工

适用于：胸牌制作、建筑模型、亚克力切割、电子治具、标识业、电子教学等行业

- 2 可选配在台面上加水槽，适用于雕刻大理石、玻璃等。

*welded steel tube fuselage with thick, by giant planer processing to ensure high precision machine tools, steel strong;

*machine adopts imported high-precision ball screw, rail, smooth motion, higher precision;

*whole dust structure axes are used to ensure a long life of the machine;

*excellent mechanical and electrical design, featuring a variety of electrical accessories, to minimize the failure rate;

*with the breakpoint memory, power outages continued carving of processing time and other functions, to ensure processing in unexpected situations

applies to: badge making, architectural models, acrylic cutting, electronic governance, identify industry, e-learning industry

optional on the table plus the sink for marble, glass, etc.

技术参数：

型号 (type)	lb-1212/lb-1218	lb-1224
x/y轴行程	1200mm*1200mm/	1200mm*2400mm
xy axle distance	1200mm*1800mm	
z轴行程	150mm	150mm
z axle distance		
最大速度	10.0(m/min)	10.0(m/min)
maximum speed		
分辨率	0.05mm	0.05mm
differentiate efficiency		
处理器	pci/dsp(32m,128m)	pci/dsp(32m,128m)
processing unit		
传动方式	丝杆传动	丝杆传动
transmission belt	screw driver	screw driver
驱动方式	步进	步进
driving style	step	step
导轨	圆轨	圆
guide	circular guide	circular guide
接口界面	win/usb	win/usb
interface screen		
软件运行环境	windows2000/xp/98	windows2000/xp/98
software working condition		
雕刻指令	g-code/hp-gl	g-code/hp-gl
carving orders		
功耗(不含主轴)	1000w	1200w
power consume(no major axle		
主轴	1500w(无刷水冷)	2200w(无刷水冷)

major axle	1500w(water-colded)	2200w(water-colded)
主轴转速	0-24000(转/分)	0-24000(转/分)
major axle speed	0-24000(circle/min)	0-24000(circle/min)
刀具径	3.175/4/6mm	3.175/4/6/8/10/12.7mm
carving diameter		
电源	220v/50hz	220v/50hz
power source		