

# LS连接器GB35L-40S-H08优势供应

产品名称	LS连接器GB35L-40S-H08优势供应
公司名称	北京一祥聚辉科贸有限公司
价格	.10/只
规格参数	
公司地址	北京海淀区宝盛里19号楼兴缘写字楼210室
联系电话	010-82916312 16622895058

## 产品详情

连接器，供应LS原装连接器

Description High voltage, sealed, electromagnetically shielded connector for BOP components on FCEV systems

Features - Electromagnetically shielded connector with metal housing- Sliding mount construction - Contact reliability ensured against severe vibration and high temperatures by using strip-bbbb contact elements - Easy bolt-on side connector Benefits - EMI shielding with bundled shield - Unit side connector easily integrates into BOP components - Low contact resistance and voltage - Compact size with bundle shielding

Specification

Type

Unit Side

Wire Side

Male

Female

Poles

2P, 3P

Voltage rating

~600V

~600V

Current rating

10A

10A

Applicable wire size

1.25?

Shielding effectiveness

40dB

## 2. 40A Connector 40A(2P) Male 40A(2P) Female

Description High-voltage, sealed, electromagnetically shielded connector for inverters / converters and other applications on HEV and FCEV systems. Features- Electromagnetically shielded connector- Tamper-resistant CPA- Contact reliability ensured against severe vibration and high temperatures by using a multiple contact terminal Benefits- EMI shielding with either an independent or bundled shield - Tamper-resistant CPA prevents removal by customers or vandals- Unit side connector easily integrates into the battery or inverter- Low contact resistance and voltage Specification

Type	Unit	Side Wire	Side Male	Female	Poles	2P, 3P, 4P	2P, 3P, 4P	Voltage rating	~600V	~600V	C
Current rating	35~40A	35~40A	35~40A	35~40A	3~8?	3~8?	3~8?	Shielding effectiveness	40dB	40dB	

## 3. 65A Connector 65A(2P) Male

65A(2P) Female Description High-voltage, sealed, electromagnetically shielded connector for batteries and inverters on HEV systems. Features- Electromagnetically shielded connector with metal housing- Tamper-resistant CPA- Contact reliability ensured against severe vibration and high temperatures by using strip-bbbb contact elements- Easy bolt-on side connector Benefits- EMI shielding with an independent shield - Tamper-resistant CPA prevents removal by customers or vandals- Unit side connector easily integrates into a battery or inverter - Low contact resistance and voltage - Compact size with high performance contact providing high conductivity