

# 026/1-A-STB-1-0氧传感器GE PANAMETRICS DELTA F

产品名称	026/1-A-STB-1-0氧传感器GE PANAMETRICS DELTA F
公司名称	北京域能汇通科技有限公司
价格	9999.00/个
规格参数	品牌: PANAMETRICS 型号: 026/1ASTB10 产地: 美国
公司地址	北京市朝阳区立清路8号3-2205
联系电话	86-010-65911327-101 18614088757

## 产品详情

026/1-A-STB-1-0?????GE PANAMETRICS DELTA F

026/1-A-STB-1-0?????GE PANAMETRICS DELTA F

?????????????????GE??, ??????,  
???Bently  
NevadaTM;????Xinhua;???DruckTM; PanametricsTM; RHEONIKTM; ??????Everest VITTM;  
HockingTM; NutronikTM,??

GE?????????????????GE????????25????????40????????????????????,?????????????GE????????????????????????????????  
??

705-1099-03 POTTING ASSY PREAMP GF 20

POTTING ASSY PREAMP GF 20 705-1099-03 (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 21.12

ASSY MANIFOLD WM FLUXLESS 705 952 04(duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 21.12

705 1045 ASSEMBLY LCD DF/GX868 (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD.21/12

CD957A HP Designjet 705 Lt Cyn Prnthd & Cleaner (ink cartgwith printhead)

CD956A HP Designjet 705 Yellow Prnthd & Cleaner (ink cartg with printhead)

705-1099-03 POTTING ASSY PREAMP GF 20(duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 21.12

705-684 ASSEMBLY DISPLAY (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 21.12

Power Supply PCB 705-792 MMS35 IS

705 1045 ASSEMBLY LCD DF/GX868 FLOWMETER (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 21.12

POTTING ASSY PREAMP GF 20 705 1099 03 (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 7.1.2

705 1326 01 ZIRCONIUM OXIDE OXYGEN SENSOR ASSEMBLY FOR USE WITH SERIES 300

PANEL MOUNT ADAPTER ASSEMBLY MTS6 705 1297 00

705 805 UNIVERSAL POWER SUPPLY BATTERY CHARGER WITH CABLE AND CONNECTOR

POTTING ASSY PREAMP GF 20 705 1099 03 (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 21.12.2013

456-005-705 - REPLICATION MANAGER: VNX5300 - BUILT-IN SW (PARTS OF COMPUETER NETWORKING EQUIPMENT)

705 1054 02 PM880 BATTERY CHARGER 230 VAC

705-1099-03 POTTING ASSY PREAMP GF 20-PART OF FLOW MTR (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 21.12.2013

705-1099-03 POTTING ASSY PREAMP GF 20 -PART OF FLOW MTR (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 21.12.201

705 -1081-03 PREAMPLIFIER FOR THE CTF878 CLAMP-ON GAS (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 7.1.2

705 1045 ASSEMBLY LCD DF/GX868 (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 7.1.2

705-1099-03 POTTING ASSY PREAMP GF20 (SPARE FOR ULTRASONIC FLOW MTR TAG NO. 144-DFT-450)

705 1326 01 ZIRCONIUM OXYGEN SENSOR ASSEMBLY FOR USE WITH SERIES 300 OR OXYUAK390 FLUE GAS ANALYSER TYPE 1 STD GLASS

G705- 4306 - 1000- NCR IGAGEMARK ARCHIVE MEDIA TIER RA10 UPGRADE TO 5M ITEMS/DAY (SOFTWARE PAPER LICENSE FOR ATM)

G705- 3000- 0000- NCR IMAGEMARK ARCHIVE MEDIA DEL BASE (SOFTWARE PAPER LICENSE FOR ATM)

G705- 3020- 0000- NCR IMAGEMARK ARCHIVE MEDIA DEL NCR CD 5K(SOFTWARE PAPER LICENSE FOR ATM)

705 1045 ASSEMBLY LCD DF/GX868 (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DTD 7.1.2014)

PREAMPLIFIER FOR THE CTF878 CLAMP ON GAS FLOWMETER MOUNTED IN CERTIFIED JUNCTION BOX FOR HAZARDOUS AREAS NEMA 4 705 1081

705-952-04 ASSY MANIFOLD WM FLUXLESS

705 952 04 ASSY MANIFOLD WM FLUXLESS

705 799 MMS351S DISPLAY ASSEMBLY

705 907 01 assy input output cga351 rm

456-005-705 - REPLICATION MANAGER:VNX5300 (BUILTIN SOFTWARE) - FOR CAPTIVE CONSUMPTION

FLOW METERS - BATTERY PACK PM880 ( 705-1023 ) ( 200-075 )

MMS3 FRONT PANEL ASSEMBLY WITH POWER SWITCH -705-728-02 (PART OF MOISTURE ANALYSER)

705-704 04 MIS1 FRONT PANEL ASSEMBLY FOR AC UNITS WITH POWER SWITCH KEYPAD AND DISPLAY FOR RACK BENCH AND PANEL PACKAGE

705-728 02 MMS3 FRONT PANEL ASSEMBLY WITH POWER SWITCH KEYPAD DISPLAY AND DISPLAY PCB FOR RACK BENCH OR PANEL PACKAGE

POTTING ASSY PREAMP GF 20 705 1099 03

705-805 UNIVERSAL POWER SUPPLY BATTERY CHARGER WITH CABLE AND CONNECTOR

705-1297-00 MTS6 PANEL MOUNT ADAPTER ASSEMBLY

MMS3 FRONT PANEL ASSEMBLY WITH POWER SWITCH KEYPAD DISPLAY AND DISPLAY PCB FOR RACK BENCH OR PANEL PACKAGE 705 728 02

MIS1 FRONT PANEL ASSEMBLY FOR AC UNITS WITH POWER SWITCH KEYPAD AND DISPLAY FOR RACK AND PANEL PACKAGE 705 704 04

705-684 ASSEMBLY DISPLAY

705-1326-01 ZIRCONIUM OXIDE OXYGEN SENSOR ASSEMBLY FOR USE WITH SERIES 300 OR OXYTRAK390 FLUE GAS ANALYSER

705-1326 01 ZIRCONIUM OXIDE OXYGEN SENSOR ASSEMBLY FOR USE WITH SERIES 300 OR OXYTRAK390 FLUE GAS ANALYSER TYPE I STD GA

705-1045 ASSEMBLY LCD DF/GX868

705-841 ASSEMBLY DISPLAY

POTTING ASSY PREAMP GF 20 705-1099 03

ASSY GF868 ENCLOSURE W/KEYPAD 705 778 35

ASSEMBLY LCD DF/GX868 705 1045

705-805 UNIVERSAL POWER SUPPLY/BATTERY CHARGER WITH CABLE AND CONNECTOR

705-1326-01 ZIRCONIUM OXIDE OXYGEN SENSOR ASSEMBLY FOR USE WITH SERIES 300 OR OXYTRAK  
390 FLUE GAS ANALYSER-TYPE 1 STD G

T5S 90 10 51.0 HT TI 1-1-2-2-0 T5S/90 DEG HEAD ANGLE/100 KHZ FREQUENCY (QTY 2) (duty protest file  
no.S/3-GEN.1280/13-14

T5 90 10 45.HT TI 1-1-2-2-0 T5S/90 DEG HEAD ANGLE/100 KHZ FREQUENCY/45 INCHES (QTY 2) (duty  
protest file no.S/3-GEN.128

T5S 18 10 18.0 HT TI 1 1 2 2 0 T5S/STRAIGHT HEAD 180 DEG /100 KHZ FREQUENCY )(duty protest file  
no.S/3-GEN.1280/13-14 GR

T5 90 10 41 NT TI 1 1 2 2 0 T5/90 DEG HEAD ANGLE 100 KHZ FREQUENCY 41 INCHES NORMAL RANGE  
55 TO 150 DEG C (67 TO 302 DEG

BWTI-1/1T-02-N-B-UX-V-2-0 BWT1/1 straight thread/0.2 MHz operating frequency (GAS Applications)fNormal  
Temperature

T5-90-10-37-HT-TI-1-1-2-2S T5/90 DEG HEAD ANGLE/100 KHZ FREQUENCY /37 INCHES/HIGH -SPARES  
FOR CRUDE PETROLEUM REFINERY

straight thread BWTI-1/1T-02-N-B-UX-V-2-0 BWT1/1 /0.2 MHz operating frequency (Gas Applications) Normal  
Temperature (du

TS-90-10-37-TI-1-1-2-2-0 T5/90 DEG HEAD ANGLE/100 KHZ FREQUENCY /37 INCHES / NORMAL RANGE  
55 TO 150 DEG no.S/3-GEN.1280

BWT1 1/T 05 N B UX V-2-0 BWTI/1 STRAIGHT THREAD 0.5 MHZ OPERATING FREQUENCY (LIQUID  
APPLICATIONS) no.S/3-GEN.1280/13-14

T5 90 10 37 HT TI 1-1-2-2-0 T5/90 DEG HEAD ANGLE 100 KHZ FREQUENCY /37 INCHES HIGH  
TEMPERATURE RANGE 70 TO 280 DEG C (9

T5 18 10 16 NT TI 0 0 0 2 0 T5/STRAIGHT HEAD 180DEG/100JHZ FREQUENCY 16/INCHES /NORMAL (duty  
protest file no.S/3-GEN.12

T5S-18-10-36-0 NT-HC-EX-S (S= HASTELLOY C-276) T5S/STRAIGHT HEAD 180 DEG/100 KHZ  
FREQUENCY INCHES NORMAL RANGE -55 TO 1

T5S 18 10 36.0 NT HC 2 1 2 2 0 T5S/STRAIGHT HEAD 180 DEG /100 KHZ FREQUENCY )(duty protest file no.S/3-GEN.1280/13-14 GR

BWTI-1/1T-05-N-B-EX-V-A-0 BWT1/1 straight thread/0.5 MHz operating frequency (Liquid Applications)fNormal Temperature (

ACC OF RADIO FREQUENCY LIASION GENERATOR- ACCESS 6996T FINAL PK-TUNNELING TOOL 5L

BWT1 1/T 05 N B EX V A O BWTI/1 STRAIGHT THREAD 0.5 MHZ OPERATING FREQUENCY (duty protest file no.S/3-GEN.1280/13-14 GR

BWTI-1/1T-05-N-B-EX-V-A-0 BWT1/1 straight thread/0.5 MHz operating frequency (Liquid Applications)fNormal Temperature d

T5-90-10-41-HT-TI-EX-0 T5/90 deg head angle/100 KHZ frequency/41 Inches/High Temperature Range: -70 to 280 deg C (-94 t

T5 90 10 49 HT TI EX 0 T5/90 DEG HEAD ANGLE 100 KHZ FREQUENCY /49 INCHES HIGH TEMPERATURE RANGE 70 TO 280 DEG C (94 TO 5

T5 90 10 37 HT TI EX 0 T5/90 DEG HEAD ANGLE 100 KHZ FREQUENCY /37 INCHES HIGH TEMPERATURE RANGE 70 TO 280 DEG C (94 TO 5

T5S 90 10 45.0 LT TI EX 0 T5S/90 DEG HEAD ANGLE/100 KHZ FREQUENCY (duty protest file no.S/3-GEN.1280/13-14 GR.VB ACC DT

BWTI-1/1T-05-N-B-EX-V-A-0 BWT1/1 straight thread/0.5 MHz operating frequency (Liquid Applications)fNormal Temperature

T5S-18-10-22.0-NT-TI -EX-0 T5S/Straight head; 180 deg/100 KHz frequency/<> inches/Normal Range: -55 to 150 deg C (-67 t

T5S 90 10 45.0 LT TI EX 0 T5S/90 DEG HEAD ANGLE/100 KHZ FREQUENCY INCHES/LOW TEMPERATURE RANGE 220 TO 120 DEG C (364 TO

T5\*3440900 T5/90 deg head angle/100 KHz frequency/41 Inches/High Temperature Range: -70 to 280 deg C (-94 to 536 deg F)

T5 90 10 45 HT T1 00 0 T5/90 DEG HEAD ANGLE/100 KHZ FREQUENCE /45 INCHES HIGH TEMPERATURE RANGE 70 TO 280 DEG C (94 TO 5

FLOW METERS - T5/90 DEG HEAD ANGLE /100KHZ FREQUENCY/45 INCHES/HIGH TEMPERATURE RANGE: -70 TO 280 DEG C ( -94 TO 536 DEG

T5-90 10 37 NT TI EX 0 T5/90 DEG HEAD ANGLE 100 KHZ FREQUENCY 37 INCHES NORMAL RANGE 55 TO 150 DEG C (67 TO 302 DEG F)ST

T5-18-10-36-NT-TI-EX-0 T5/Straight head; 180 deg/100 KHz frequency/36 Inches/Normal Range: -55 to 150 deg C (-67 to 302

BWTI-1/1T-05-N-B-EX-V-A-0 BWT1/1 straight thread/0.5 MHz operating frequency (Liquid Applications)fNormal

Temperature -

T5-18-10-36-NT-TI-00-0 T5/Straight head; 180 deg/100 KHz frequency/36 Inches/Normal Range: -55 to 150 deg C (-67 to 302

T5-90 10 41 NT TI 00 0 T5/90 DEG HEAD ANGLE 100 KHZ FREQUENCY 41 INCHES NORMAL RANGE 55 TO 150 DEG C (67 TO 302 DEG F)ST

T5S-18-10-37.0-NT-TI-EX-0 T5/Straight head:180deg/100 KHz frequency/inches/Normal Range: -55 to 150 deg C (-67 to 302 d

BWT1-1/1T-05-N-B-EX-V-A-0 BWT1/1 straight thread/0.5 MHz operating frequency (Liquid Applications)/Normal Temperature -