

# 美国PCB 086C04力锤传感器体验硬实力

产品名称	美国PCB 086C04力锤传感器体验硬实力
公司名称	上海持承自动化设备有限公司
价格	200.00/个
规格参数	PCB:5 mV/lbf 086C04: ± 1000 lbf pk 美国: 22 kHz
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

## 产品详情

美国PCB 086C04力锤传感器体验硬实力

Modally Tuned Impulse Hammer w/force sensor and tips, 0 to 1k lbf, 5 mV/lbf (1.1 mV/N)

Sensitivity: ( ± 15%) 5 mV/lbf (1.1 mV/N)

Measurement Range: ± 1000 lbf pk ( ± 4448 N pk)

Hammer Mass: 0.34 lb (0.16 kg)

English

Sensitivity ( ± 15 %)

5 mV/lbf

Measurement Range

± 1000 lbf pk

Resonant Frequency

22 kHz

Non-Linearity	1 %
Electrical Excitation Voltage	20 to 30 VDC
Constant Current Excitation	2 to 20 mA
Output Impedance	<100 Ohm
Output Bias Voltage	8 to 14 VDC
Discharge Time Constant	2000 sec
Physical Sensing Element	Quartz
Sealing	Epoxy
Hammer Mass	0.34 lb
Head Diameter	0.62 in
Tip Diameter	0.25 in
Hammer Length	8.5 in
Electrical Connection Position	Bottom of Handle

Extender Mass Weight 2.6 oz

Electrical Connector BNC Jack

Supplied		
084A08	Extender - Steel, 0.6" Diameter	(1)
084B03	Hard Tip- Hard (S.S)	(1)
084B04	Hammer Tip- Medium (White Plastic)	(1)
HCS-2	Calibration of Series 086 instrumented impact hammers	(1)
081B05	Mounting Stud (10-32 to 10-32)	(2)
084C05	Hammer Tip- Soft (Black)	(2)
084C11	Hammer Tip- Supersoft (Red)	(2)
085A10	Vinyl Cover For Medium Tip (Blue)	(2)

我公司主要经营变频器，纠偏，触摸屏，PLC，伺服，限位开关，传感器，编码器等