

# C5210-0010 | 19英寸滑入式工业PC精实能效

产品名称	C5210-0010   19英寸滑入式工业PC精实能效
公司名称	上海持承自动化设备有限公司
价格	632.00/台
规格参数	倍福:Beckhoff C5210:C5210-0010 德国:GERMANY
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

## 产品详情

C5210-0010 | 19英寸滑入式工业PC精实能效

C5210-0000 Processor available

Intel Celeron, 2 Cores (TC3: 50\*) or Intel Pentium, 2 Cores (TC3: 50\*) or Intel Core i3, 2 Cores (TC3: 60\*) or Intel Core i5, 4 Cores (TC3: 70\*) or Intel Core i7, 4 Cores (TC3: 80\*) (6th/7th generation)

C5210-0020

Intel Celeron, 2 Cores (TC3: 50\*) or Intel Core i3, 2 Cores (TC3: 60\*) or Intel Core i5, 2 Cores (TC3: 70\*) or Intel Core i7, 4 Cores (TC3: 80\*) (4th generation)

C5210-0010

Intel Celeron, 2 Cores (TC3: 50\*) or Intel Core i3, 2 Cores (TC3: 60\*) or Intel Core i5, 2 Cores (TC3: 70\*) or Intel Core i7, 4 Cores (TC3: 80\*)

C5210-0010 19-inch slide-in Industrial PC Housing

slide-in housing for 19-inch racks, 1 rack unit  
all drives accessible from the front  
2 removable frames for hard disks  
1 DVD drive slot, 2 USB sockets, reset key and ATX key behind a lockable front flap  
status LEDs  
all connectors at the rear side  
2 PCIe module slots to plug-in Beckhoff PCIe modules or to lead out interfaces of the motherboard ex factory  
protection class IP 20  
operating temperature 0...55 °C

Features	<p>dimensions (W x H x D) 482.7 x 44 x 493.8 mm (19" x 1.7" x 19.44")</p> <p>depth behind the front 471.3 mm (18.56 " )</p> <p>processor Intel Celeron B810 1.6 GHz, 2 cores (TC3: 50)</p> <p>3-inch motherboard for 2nd and 3rd Generation Intel Core i3, Core i5, Core i7 or Celeron</p> <p>1 Mini PCI slot free for cards installed ex factory</p> <p>2 GB DDR3 RAM, expandable to 16 GB</p> <p>graphic adapter integrated inside the Intel processor, 1 DVI-I connector</p> <p>on-board dual Ethernet adapter with 2 x 10/100/1000BASE-T connector</p> <p>on-board SATA RAID 1 controller, Intel Rapid Storage Technology</p> <p>hard disk, 3-inch, 1 TB</p> <p>4 serial ports RS232 on-board, 1 of these RS232 ports is led out with D-sub 9 connector</p> <p>4 USB 2.0 ports at the rear side and 2 USB 2.0 ports behind the front flap</p> <p>100...240 V AC full range power supply</p>
C9900-C542	<p>processor 2nd Generation Intel Core i3 2330E, 2.2 GHz, 2 cores (TC3: 60), instead of Intel Celeron B810 1.6 GHz (TC3: 50)</p>
C9900-C542	<p>processor 2nd Generation Intel Core i5 2510E, 2.5 GHz, 2 cores (TC3: 70), instead of Intel Celeron B810 1.6 GHz (TC3: 50)</p>
C9900-C543	<p>processor 2nd Generation Intel Core i7 2710QE, 2.1 GHz, 4 cores (TC3: 80), instead of Intel Celeron B810 1.6 GHz (TC3: 50)</p>
C9900-C565	<p>processor 3rd Generation Intel Celeron 1020E, 2.2 GHz, 2 cores (TC3: 50), instead of Intel Celeron B810 1.6 GHz (TC3: 50)</p>
C9900-C544	<p>processor 3rd Generation Intel Core i5 3610ME 2.7 GHz, 2 cores (TC3: 70), instead of Intel Celeron B810 1.6 GHz (TC3: 50)</p>
C9900-C545	<p>processor 3rd Generation Intel Core i7 3610QE 2.3 GHz, 4 cores (TC3: 80), instead of Intel Celeron B810 1.6 GHz (TC3: 50)</p>
C9900-R249	<p>memory extension to 4 GB DDR3 RAM, instead of 2 GB, requires a 64 bit operating system or only 3 GB are addressable</p>
C9900-R250	<p>memory extension to 8 GB DDR3 RAM, instead of 2 GB, requires a 64 bit operating system</p>
C9900-R251	<p>memory extension to 16 GB DDR3 RAM, instead of 2 GB, requires a 64 bit operating system</p>
FC9062	<p>Gigabit Ethernet PCIe module for PCs with Beckhoff PCIe module slots, 2-channel, PCI Express x1 bus</p>
C9900-E277	<p>USB 3.0 PCIe module- 2-port USB 3.0 interfaces- USB transfer rate up to 5 Gbit/s for USB 3.0-</p>

C9900-D118	compatible to all USB standards- delivers up to 1 A supply current at each USB port multi DVD drive slimline, reads CD-ROM and DVD-ROM, reads and writes CD-R/-RW, DVD-R/+R/-RW/+RW 4.7 GB and DVD-R/+R DL 8.5 GB
C9900-M712	telescope rails for C5210 and C5240, rails including bracket set for 19-inch rack assembly
C9900-E233	1 serial port RS232 of the motherboard led out at the connection section of a C5210, C65x5, CP2xxx, CP62xx or CP67xx-xxxx-0040/-0050
C9900-E234	2 USB ports of the motherboard led out at the connection section of a C5210, C65x5, CP2xxx, CP62xx or CP67xx-xxxx-0040/-0050
C9900-E237	additional DVI-D plug led out on a module bracket, cannot be ordered in combination with an additional display port interface
C9900-E240	Serial port COM2 RS232, optically linked, overload protection, D-sub 9-pin connector.
C9900-E241	Serial port COM2 RS485, optically linked, overload protection, D-sub 9-pin connector. Configuration as an end point without echo: echo off, auto send on, always send off, auto receive on, always receive off, termination on
C9900-E242	Serial port COM2 RS422, optically linked, overload protection, D-sub 9-pin connector. Configuration as a full duplex end point: echo on, auto send off, always send on, auto receive off, always receive on, termination on
C9900-Z411	adapter plug DVI-I to VGA
C9900-Z413	adapter cable DVI-I to DVI and VGA, 15 cm
FC9071	Gigabit Ethernet PC interface card, 10/100/1000 Mbit/s, 1-channel, PCIe interface, occupies the fieldbus connection area.
C9900-R230	memory module NOVRAM for fail-safe storage of process data, 128 kB, Mini PCI plug-in card
C9900-R231	memory module NOVRAM for fail-safe storage of process data, 256 kB, Mini PCI plug-in card
C9900-R232	memory module NOVRAM for fail-safe storage of process data, 512 kB, Mini PCI plug-in card
C9900-H201	hard disk drive, 3-inch, 2 TB, instead of hard disk 1 TB
C9900-H202	hard disk drive, 3-inch, 4 TB, instead of hard disk 1 TB, requires a 64 bit operating system and UEFI instead of BIOS
C9900-B528	BIOS for booting from storage media bigger than 2 TB, UEFI activated
C9900-H152	additional hard disk drive, 3-inch, 1 TB
C9900-H203	additional hard disk drive, 3-inch, 2 TB
C9900-H204	additional hard disk drive, 3-inch, 4 TB
C9900-M629	removable frame for a 2-inch SSD, instead of

	removable frame for a 3-inch hard disk
C9900-H749	solid-state disk SSD, 3D flash, 2-inch, 240 GB
C9900-H745	solid-state disk SSD, 3D flash, 2-inch, 480 GB
C9900-H759	solid-state disk SSD, 3D flash, 2-inch, 960 GB
C9900-H751	solid-state disk SSD, 3D flash, 2-inch, 240 GB, instead of 3-inch hard disk
C9900-H747	solid-state disk SSD, 3D flash, 2-inch, 480 GB, instead of 3-inch hard disk
C9900-H761	solid-state disk SSD, 3D flash, 2-inch, 960 GB, instead of 3-inch hard disk
C9900-H700	solid-state disk SSD, SLC flash, 2-inch, 32 GB
C9900-H705	solid-state disk SSD, SLC flash, 2-inch, 64 GB
C9900-H735	solid-state disk SSD, SLC flash, 2-inch, 128 GB
C9900-H702	solid-state disk SSD, SLC flash, 2-inch, 32 GB, instead of 3-inch hard disk
C9900-H707	solid-state disk SSD, SLC flash, 2-inch, 64 GB, instead of 3-inch hard disk
C9900-H737	solid-state disk SSD, SLC flash, 2-inch, 128 GB, instead of 3-inch hard disk
C9900-P208	24 V DC power supply, instead of 100 – 240 V AC full range power supply, occupies one serial port
C9900-P209	24 V DC power supply with integrated UPS, instead of 100 – 240 V AC full range power supply, occupies one serial port
C9900-U330	battery pack for PCs with 24 V power supply and integrated UPS C9900-P209 or C9900-U209, external, for DIN rail mounting, 3.4 Ah, operating temperature 0...50 ° C
C9900-U120	uninterruptible power supply UPS, external, 230 V
C9900-U122	uninterruptible power supply UPS, external, 115 V
C9900-M623	wall mounting frame for uninterruptible power supply C9900-U120, C9900-U122 and C9900-U124