

## C6150-0050 | Control cabinet Industrial PC

产品名称	C6150-0050   Control cabinet Industrial PC
公司名称	上海持承自动化设备有限公司
价格	462.00/台
规格参数	倍福:Beckhoff C6150:C6150-0050 德国:GERMANY
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

## 产品详情

## C6150-0050 | Control cabinet Industrial PC

Variable processor available

Intel Celeron, 2 Cores (TC3: 50\*) or Intel Pentium, 2 Cores (TC3: 50\*) or Intel Core i3, 2 Cores (TC3: 60\*) or Intel Core i5, 4 Cores (TC3: 70\*) or Intel Core i7, 4 Cores (TC3: 80\*) (6th/7th generation)

C6150-0060

Intel Pentium, 2 Cores (TC3: 50\*) or Intel Core i3, 2 Cores (TC3: 60\*) or Intel Core i5, 2 Cores (TC3: 70\*) or Intel Core i5, 4 Cores (TC3: 70\*) or Intel Core i7, 4 Cores (TC3: 80\*) (4th generation)

C6150-0050

Intel Celeron, 2 Cores (TC3: 50\*) or Intel Core i3, 2 Cores (TC3: 60\*) or Intel Core i5, 2 Cores (TC3: 70\*) or Intel Core i7, 4 Cores (TC3: 80\*)

C6150-0050 Control cabinet PC Housing

7-slot ATX Industrial PC for control cabinet installation  
all slots for full-length plug-in cards  
drives and plug-in cards easily accessible  
all connectors on the top  
detailed PC configuration information on the front  
status LEDs and protected reset key  
card holders, actuated without tools  
protection class IP 20  
operating temperature 0...55 °C

## Features

weight of the basic configuration 15 kg (33.1 lbs)  
dimensions (W x H x D) 383 x 423 x 265 mm  
(15.1" x 16.7" x 10.5")

processor Intel Celeron B810 1.6 GHz, 2 cores  
(TC3: 50)

ATX motherboard for 2nd and 3rd Generation  
Intel Core i3, Core i5, Core i7 or Celeron  
2 PCIe x1 slots, 1 PCIe x4 slot, 1 PCIe x16 slot and  
3 PCI slots free

2 GB DDR3 RAM, expandable to 16 GB

graphic adapter integrated inside the Intel  
processor, 1 DVI-I, 1 DVI-D and 1 DisplayPort  
connector. 2 of the 3 connectors are usable at the  
same time.

on-board dual Ethernet adapter with 2 x  
10/100/1000BASE-T connector

on-board SATA RAID 1 controller, Intel Rapid  
Storage Technology

hard disk, 3-inch, 1 TB

4 serial ports RS232 on-board, 1 of these RS232  
ports is led out with D-sub 9 connector; 14 USB  
2.0, 4 of these USB ports are led out

PS/2 keyboard socket and PS/2 mouse socket

100...240 V AC full range power supply