

PowerFlex 753交流变频器美国AB罗克韦尔选型资料

产品名称	PowerFlex 753交流变频器美国AB罗克韦尔选型资料
公司名称	上海持承自动化设备有限公司
价格	225.00/台
规格参数	罗克韦尔:rockwell AB:PowerFlex 75 美国:USA
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

产品详情

PowerFlex 753 交流变频器

PowerFlex 753 交流变频器在需要安全功能的通用应用项目中既经济实用，又易于使用。它们标配有内置 I/O，有助于降低工程设计成本、缩短机器上市时间并满足最终用户对机器生产力的更高要求，是机器制造商和系统集成商的理想选择。针对空间有限的低功率应用项目，可选择使用尺寸优化的变频器。双端口 EtherNet/IP 选件模块提供了灵活而经济实用的 EtherNet/IP 网络利用方法。

特性

额定功率：

200 - 240 V：0.37 到 132 kW / 0.5 到 200 Hp / 2.2 到 477 A

380 到 480V：0.75 到 250 kW / 1.0 到 350 Hp / 2.1 到 456 A

600V：1.0...300 Hp / 1.7...289 A

690V：7.5...250 kW / 12...263 A

IP00/IP20 NEMA/UL 开放式，法兰安装，IP54 NEMA/UL 类型 12

双端口 EtherNet/IP 选件模块有助于您利用 EtherNet/IP 网络，最大限度地减少管理型交换机的数量，并减少使用设备级环网 (DLR) 时的接线需求

V/Hz 控制、采用 FORCE 技术的矢量控制和无传感器矢量控制

预测性诊断可延长冷却风扇和继电器输出的寿命

基于插槽的架构提供了三个可选插槽，可用于反馈、安全、通信、附加 I/O 或辅助电源

通过集成式 LCD 人机接口模块 (HIM)、DriveTools SP 软件、Connected Components Workbench 软件或 Studio 5000 Logix Designer 软件进行配置和编程

提供嵌入式安全选件

安全转矩中断功能经过认证符合 PLe/SIL3 CAT 3

安全转速监视器将安全断开扭矩功能与采用 Rockwell Automation

安全转速控制核心技术的嵌入式安全继电器组合在驱动器的一个嵌入式硬件选件中。经认证符合 PLe/SIL3 CAT 4

20F11FB015JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 15.3 Amps, 5 HP ND, 3 HP HD, 240 (208) VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FB022JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 22 Amps, 7.5 HP ND, 5 HP HD, 240 (208) VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FB028JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 28 Amps, 10 HP ND, 7.5 HP HD, 240 (208) VAC, 3 PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FB042JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 42 Amps, 15 HP ND, 10 HP HD, 240 (208) VAC, 3 PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FB054JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 54 Amps, 20 HP ND, 15 HP HD, 240 (208) VAC, 3 PH, Frame 4, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FB070JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 70 Amps, 25 HP ND, 20 HP HD, 240 (208) VAC, 3 PH, Frame 5, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FB080JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 80 Amps, 30 HP ND, 25 HP HD, 240 (208) VAC, 3 PH, Frame 5, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FB2P2JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 2.2 Amps, 0.5 HP ND, 0.5 HP HD, 240 (208) VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FB4P2JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 4.2 Amps, 1 HP ND, 0.5 HP HD, 240 (208) VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FB6P8JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 6.8 Amps, 2 HP ND, 1 HP HD, 240 (208) VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FB9P6JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 9.6 Amps, 3 HP ND, 2 HP HD, 240 (208) VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC011JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 11.5 Amps, (Fr1 5.5kW ND, 4kW HD/Fr2 5.5kW ND, 5.5kW HD), 400 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC015JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 15.4 Amps, 7.5kW ND, 5.5kW HD, 400 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC022JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 22 Amps, 11kW ND, 7.5kW HD, 400 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC030JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC

Terminals, Flange Type, 30 Amps, 15kW ND, 11kW HD, 400 VAC, 3 PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC037JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 37 Amps, 18.5kW ND, 15kW HD, 400 VAC, 3 PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC043JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 43 Amps, 22kW ND, 18.5kW HD, 400 VAC, 3 PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC060JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 60 Amps, 30kW ND, 22kW HD, 400 VAC, 3 PH, Frame 4, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC072JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 72 Amps, 37kW ND, 30kW HD, 400 VAC, 3 PH, Frame 4, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC085JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 85 Amps, 45kW ND, 37kW HD, 400 VAC, 3 PH, Frame 5, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC104JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 104 Amps, 55kW ND, 45kW HD, 400 VAC, 3 PH, Frame 5, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC2P1JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 2.1 Amps, (Fr1 0.75kW ND, 0.37kW HD/Fr2 0.75kW ND, 0.75kW HD)", 400 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC3P5JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 3.5 Amps, (Fr1 1.5kW ND, 0.75kW HD/Fr2 1.5kW ND, 0.1.5kW HD), 400 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC5P0JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 5 Amps, (Fr1 2.2kW ND, 1.5kW HD/Fr2 2.2kW ND, 2.2kW HD), 400 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FC8P7JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 8.7 Amps, (Fr1 4kW ND, 2.2kW HD/Fr2 4kW ND, 4kW HD), 400 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD011JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 11 Amps, (Fr1 7.5HP ND, 5HP HD/Fr2 7.5HP ND, 7.5HP HD), 480 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD014JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 14 Amps, 10HP ND, 7.5HP HD, 480 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM)