

20F11FB015JA0NNNNN美国AB罗克韦尔变频器技术资料

产品名称	20F11FB015JA0NNNNN美国AB罗克韦尔变频器技术资料
公司名称	上海持承自动化设备有限公司
价格	320.00/台
规格参数	罗克韦尔:Allen-Bradle AB:20F11FB015JA 美国:USA
公司地址	上海市金山区吕巷镇干巷荣昌路318号3幢1018室
联系电话	021-59112701 13671506557

产品详情

20F11FB015JA0NNNNN美国AB罗克韦尔变频器技术资料

PowerFlex 753 交流变频器

PowerFlex 753 交流变频器在需要安全功能的通用应用项目中既经济实用，又易于使用。它们标配有内置 I/O，有助于降低工程设计成本、缩短机器上市时间并满足最终用户对机器生产力的更高要求，是机器制造商和系统集成商的理想选择。针对空间有限的低功率应用项目，可选择使用尺寸优化的变频器。双端口 EtherNet/IP 选件模块提供了灵活而经济实用的 EtherNet/IP 网络利用方法。

特性

额定功率：

200 - 240 V：0.37 到 132 kW / 0.5 到 200 Hp / 2.2 到 477 A

380 到 480V：0.75 到 250 kW / 1.0 到 350 Hp / 2.1 到 456 A

600V：1.0...300 Hp / 1.7...289 A

690V：7.5...250 kW / 12...263 A

IP00/IP20 NEMA/UL 开放式，法兰安装，IP54 NEMA/UL 类型 12

双端口 EtherNet/IP 选件模块有助于您利用 EtherNet/IP 网络，最大限度地减少管理型交换机的数量，并减少使用设备级环网 (DLR) 时的接线需求

V/Hz 控制、采用 FORCE 技术的矢量控制和无传感器矢量控制

预测性诊断可延长冷却风扇和继电器输出的寿命

基于插槽的架构提供了三个可选插槽，可用于反馈、安全、通信、附加 I/O 或辅助电源

通过集成式 LCD 人机接口模块 (HIM)、DriveTools SP 软件、Connected Components Workbench 软件或 Studio 5000 Logix Designer 软件进行配置和编程

提供嵌入式安全选件

安全转矩中断功能经过认证符合 PLe/SIL3 CAT 3

安全转速监视器将安全断开扭矩功能与采用 Rockwell Automation 安全转速控制核心技术的嵌入式安全继电器组合在驱动器的一个嵌入式硬件选件中。经认证符合 PLe/SIL3 CAT 4

20F11FD022JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 22 Amps, 15HP ND, 10HP HD, 480 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD027JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 27 Amps, 20HP ND, 15HP HD, 480 VAC, 3 PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD034JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 34 Amps, 25HP ND, 20HP HD, 480 VAC, 3 PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD040JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 40 Amps, 30HP ND, 25HP HD, 480 VAC, 3 PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD052JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 52 Amps, 40HP ND, 30HP HD, 480 VAC, 3 PH, Frame 4, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD065JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 65 Amps, 50HP ND, 40HP HD, 480 VAC, 3 PH, Frame 4, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD077JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 77 Amps, 60HP ND, 50HP HD, 480 VAC, 3 PH, Frame 5, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD096JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 96 Amps, 75HP ND, 60HP HD, 480 VAC, 3 PH, Frame 5, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD2P1JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 2.1 Amps, (Fr1 1HP ND, 0.5HP HD/Fr2 1HP ND, 1HP HD), 480 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD3P4JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 3.4 Amps, (Fr1 2HP ND, 1.5HP HD/Fr2 2HP ND, 2HP HD), 480 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD5P0JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 5 Amps, (Fr1 3HP ND, 2HP HD/Fr2 3HP ND, 3HP HD), 480 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FD8P0JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 8 Amps, (Fr1 5HP ND, 3HP HD/Fr2 5HP ND, 5HP HD), 480 VAC, 3 PH, Frame 2, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE011JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 11 Amps, 10HP ND, 7.5HP HD, 600 VAC, 3PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE017JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 17 Amps, 15HP ND, 10HP HD, 600 VAC, 3PH, Frame 3, Filtered, CM Jumper Installed, DB

Transistor, Blank (No HIM) 20F11FE022JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 22 Amps, 20HP ND, 15HP HD, 600 VAC, 3PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE027JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 27 Amps, 25HP ND, 20HP HD, 600 VAC, 3PH, Frame 4, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE032JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 32 Amps, 30HP ND, 25HP HD, 600 VAC, 3PH, Frame 4, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE041JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 41 Amps, 40HP ND, 30HP HD, 600 VAC, 3PH, Frame 5, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE052JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 52 Amps, 50HP ND, 40HP HD, 600 VAC, 3PH, Frame 5, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE1P7JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 1.7 Amps, 1HP ND, 0.5HP HD, 600 VAC, 3PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE2P7JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 2.7 Amps, 2HP ND, 1HP HD, 600 VAC, 3PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE3P9JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 3.9 Amps, 3HP ND, 2HP HD, 600 VAC, 3PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE6P1JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 6.1 Amps, 5HP ND, 3HP HD, 600 VAC, 3PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM) 20F11FE9P0JA0NNNNN PowerFlex 753 AC Drive, with Embedded I/O, Air Cooled, AC Input with DC Terminals, Flange Type, 9 Amps, 7.5HP ND, 5HP HD, 600 VAC, 3PH, Frame 3, Filtered, CM Jumper Installed, DB Transistor, Blank (No HIM)