

雕刻机木工家具制造机械设备

| | |
|------|--|
| 产品名称 | 雕刻机木工家具制造机械设备 |
| 公司名称 | 合肥赛锐数控设备有限公司 |
| 价格 | .00/个 |
| 规格参数 | 家具制造机械种类:木工铣床 品牌:赛远SIGNKEY 型号:1325WAT3 |
| 公司地址 | 安徽省合肥市新站区工业园E区34号厂房 |
| 联系电话 | 64280790 15156060264 |

产品详情

| | | | |
|----------|-------------|--------|-----------------------|
| 家具制造机械种类 | 木工铣床 | 品牌 | 赛远SIGNKEY |
| 型号 | 1325WAT3 | 是否进口 | 否 |
| 工作形式 | 全自动 | 产品类型 | 全新 |
| 电机功率 | 5.5 (kw) | 外形尺寸 | 3300*2200*1600 (mm) |
| 最大加工长度 | 2500 (mm) | 最大加工厚度 | 150 (mm) |
| 最大加工宽度 | 1300 (mm) | 重量 | 1300 (kg) |
| 送料速度 | 25米/分 | 适用范围 | 家具制造,橱柜加工,各种木门制造 |

性能特点 standard features

1.机身采用工业钢管焊接，箱式结构，承载量大

the lathe is founded by industrial pipe welding, box-type structure to ensure the high stability

2.专用仪器消除焊接应力，高精度刨床加工，不变形、精度有保证。

the special instruments to eliminate welding stress, high-precision machining planer ensure the precision and no deformation.

3.机身自重大，高速运行不抖动、更平稳。

the major machine body makes the stability and no shacking in high speed.

4. xyz采用全进口丝杆或高精度齿条出论结构、直线导轨，精度更高。

xyz all apply imported screw, high precision gear frame and linear guide ,ensure the high accuracy .

5.专业团队的机械结构设计，结构科学，外观大方。

the professional mechanical design, scientific structure and generous appearance.

适用行业 scope of application:

适用于仿古家具浮雕雕刻，木工镂花，家具制造，家具装饰、木工装饰、乐器制造、木制工艺品、吸塑灯箱3d模具制作，铝塑板加工、大型建筑模型制作等行业。

可用于大面积板材平面雕刻、实木家具雕刻、实木艺术壁画雕刻、实木雕刻、密度板免漆门雕刻、橱窗门雕刻。

widely used in antique furniture with relief carving, wood carving, furniture- processing , instrument making ,3d light box making ,

aluminum composite panel, funding mould decorative doors and windows processing etc.

特殊配置：可定制：更大幅面和特殊幅面的机型。可选配进口主轴，自动换刀，真空吸附等。

special configuration:

it can be customized more large format and special format models, and it can be optional standard configuration spindle or importing, auto-change tool system, vacuum inhaling and dust collect etc.

技术参数

| | |
|-----------------------------|------------------------------|
| 型号 model | sk-1325wat3 |
| 台面尺寸 table size | 1540 × 2640mm |
| 加工尺寸 working size | 1300 × 2500 × 130mm |
| 主轴功率 spindle voltage | 1号主轴5.5kw（风冷），2、3主轴3.7kw（风冷） |
| z向结构 z structure | 独立z轴，3汽缸联动，高精度丝杆精确对刀 |
| 主轴转速 spindle speed | 6000~24000rpm |
| 驱动 driver | 步进驱动（可选国产或进口伺服驱动） |
| 刀具直径 tool diameter | 3.175，4，6，12.7mm |
| 机体结构 structure | 工业钢管箱式结构 |
| 传动系统 transmission | 高精度齿条传动 |
| xyz导轨 xyz guiding rails | 进口直线导轨 |
| 机械精度 reposition accuracy | < 0.03/300mm |
| 雕刻速度 engraving speed | 12000mm/min |
| 数据传输 date interface | 计算机直联 |
| 指令格式 format of instructions | g代码格式或hpgl |
| 输入电源 voltage | ac220v/50hz or 380v/50hz |
| 机器净重 net weight | 1200kg |