高透明PC 高纯净度 透光率高达93%

产品名称	高透明PC 高纯净度 透光率高达93%
公司名称	东莞市华韵塑胶原料有限公司
价格	22.00/kg
规格参数	PC:高透明 PC:高纯净度 PC:透光率高达93%
公司地址	东莞市樟木头镇奥园塑金国际8栋214
联系电话	0769-87600377 13556776933

产品详情

高透明PC 高纯净度 透光率高达93%

供应PC 1239 德国拜耳 吹塑级

供应PC 2605 德国拜耳 中低粘度耐冲击 注射或挤塑成型

供应PC 2097 德国拜耳高流动, 耐高温200 FL900耐高温

供应PC 2207 德国拜耳 极低粘度,流动性极差,注射成型

供应PC 6487 德国拜耳中 粘度、紫外线稳定,易脱模,耐冲击性能好

供应PC 2405 德国拜耳 高流动 低粘度 注塑成型

供应PC 2407 德国拜耳 高流动 抗紫外线 低粘度 注塑成型

供应PC 2807 德国拜耳 中粘度 抗紫外线

供应PC 2805 德国拜耳中粘度 注射或挤塑成型

供应PC 2858 德国拜耳 食品级

供应PC 2658 德国拜耳 食品级

供应PC 2458 德国拜耳 食品级

供应PC 6485 德国拜耳 阻燃VO

供应PC 6265 德国拜耳 阻燃VO

供应PC 6557 德国拜耳中粘度易脱模阻燃V-0

供应PC 6555 德国拜耳 阻燃V0中粘度 注射或挤塑成型

供应PC 3103 德国拜耳 抗紫外线,高粘度,中高分子量

供应PC 3108 德国拜耳 抗紫外线

供应PC 3208 德国拜耳 高粘度,高分子量 挤塑 耐冲击 FDA认可,水触稳定性;

Warm Tip: The company operates a variety of engineering plastics, general plastics, raw materials market fluctuations, prices inevitably frequent fluctuations, online prices sometimes too late to update, but also hope that the majority of customers understand. On the day of the actual quotation of raw materials, details of the consultation. Solemnly Promise: The company sold raw materials are original packaging authentic materials, to eliminate all sub-brand materials, Shuikou materials, to charge good. Logistics: Pearl River Delta to arrive in one day, 3-4 days to arrive in all parts of China. Welcome to call us! PS: can provide detailed physical information and various certification reports; free sample analysis for customers and provide material type consulting services; if you need samples, product information and the same day quote, please call or on-line consultation. We would like to set up a cooperative friendship bridge with our most sincere service to create a win-win situation. Your satisfaction and trust is our harvest! Product characteristics: High viscosity (VMI 3.0), UV stability, weather resistance, Flame Retardant Grade V 0, easy demoulding, transparent grade PC, injection grade, demoulding grade material typical application: Automotive components, electronic components PC [polycarbonate] remarkable characteristics: 1. Impact Resistance property, has in the plastic impact strength value, moreover its performance is higher than the cast zinc and the cast aluminum. 2. Stable performance can be maintained in a wide range from low temperature to high temperature (- 100 $^{\circ}$ C \sim 129 ° c) . 3. Electrical properties, in a wide temperature range with excellent electrical insulation. 4. Transparent, with a few of the transparency of plastic, suitable for optical and plate use. 5. Dimensional stability, with excellent creep resistance, size almost independent of moisture absorption, temperature, time. 6. It has passed the appraisal of UL specification Subject94 in the grades of V-0, V-1, V-2, HB, 5VA and 5VB.