

角接触球轴承718系列 ZYS

产品名称	角接触球轴承718系列 ZYS
公司名称	上海沃安精密轴承有限公司
价格	.00/个
规格参数	品牌:ZYS 型号:718系列 类型:角接触球轴承
公司地址	上海市闸北区场中路3424甲号
联系电话	021-53088291 18017808803

产品详情

品牌	ZYS	型号	718系列
类型	角接触球轴承	内径	8-280 (mm)
外径	22-420 (mm)	厚度	7-65
保持架及其材料	TH玻璃纤维增强酚醛树脂	使用特性	高速
用途	机床主轴	滚动体列数	单列
滚道类型	深沟滚道	样品或现货	现货

型号	接触角		外形尺寸				额定载荷			极限		重量	
	c=15°	ac=15°	d	d	b	rsmin	rismin	a	cr	cor	脂		油
			mm							kn		r/min	kg
71800	c		10	19	5	0.30	0.10	4	1.8	1.1	75000	120000	0.005
	ac					0.30	0.10	6	1.7	1.1	70000	110000	0.005
71801	c		12	21	5	0.30	0.10	5	2	1.4	70000	110000	0.006
	ac					0.30	0.10	6	1.9	1.3	63000	95000	0.006
71802	c		15	24	5	0.30	0.10	5	2.2	1.8	60000	90000	0.007
	ac					0.30	0.10	7	2.1	1.7	53000	80000	0.007
71803	c		17	26	5	0.30	0.10	5	2.3	1.9	53000	80000	0.008
	ac					0.30	0.10	7	2.1	1.8	50000	75000	0.008
71804	c		20	32	7	0.30	0.10	7	3.9	3.4	45000	67000	0.018
	ac					0.30	0.10	9	3.7	3.2	40000	60000	0.018
71805	c		25	37	7	0.30	0.15	8	4.2	4.1	38000	56000	0.022
	ac					0.30	0.15	11	3.9	3.9	34000	50000	0.022
71806	c		30	42	7	0.30	0.15	8	4.4	4.8	32000	48000	0.025
	ac					0.30	0.15	12	4.1	4.5	28000	43000	0.025

71807	c	35	47	7	0.30	0.15	9	4.6	5.5	26000	40000	0.029
	ac				0.30	0.15	13	4.3	5.2	24000	38000	0.029
71808	c	40	52	7	0.30	0.15	10	4.8	6.2	24000	38000	0.032
	ac				0.30	0.15	14	4.5	5.8	20000	34000	0.032
71809	c	45	58	7	0.30	0.15	10	4.9	6.7	18000	34000	0.040
	ac				0.30	0.15	14	4.6	6.3	18000	30000	0.040
71810	c	50	65	7	0.30	0.15	11	7.4	10	16000	30000	0.052
	ac				0.30	0.15	17	6.9	9.5	16000	26000	0.052
71811	c	55	72	9	0.30	0.15	13	10.2	13.8	16000	26000	0.081
	ac				0.30	0.15	19	9.6	13.1	15000	24000	0.081
71812	c	60	78	9	0.30	0.15	14	13.4	18	15000	24000	0.100
	ac				0.30	0.15	21	12.6	17	14000	22000	0.100
71813	c	65	85	10	0.60	0.15	15	13.4	18.8	14000	22000	0.125
	ac				0.60	0.15	22	12.6	13.8	13000	20000	0.125
71814	c	70	90	10	0.60	0.15	16	13.8	20.3	13000	20000	0.133
	ac				0.60	0.15	24	13	19.1	12000	19000	0.133
71815	c	75	95	10	0.60	0.15	16	14.2	21.7	12000	19000	0.142
	ac				0.60	0.15	25	13.3	20.5	11000	18000	0.142
71816	c	80	100	10	0.60	0.15	17	14.5	23.1	11000	18000	0.150
	ac				0.60	0.15	26	13.6	21.8	9500	16000	0.150
71817	c	85	110	13	1.00	0.30	20	21.5	32.2	10000	17000	0.262
	ac				1.00	0.30	29	20.2	30.5	9000	15000	0.262
71818	c	90	115	13	1.00	0.30	20	21.7	33.5	9500	16000	0.274
	ac				1.00	0.30	30	20.4	31.6	8500	14000	0.274
71819	c	95	120	13	1.00	0.30	21	21.9	34.7	9000	15000	0.287
	ac				1.00	0.30	32	20.6	32.8	8500	14000	0.287
71820	c	100	125	13	1.00	0.30	22	22.5	37	8500	14000	0.301
	ac				1.00	0.30	33	21.2	34.9	8000	13000	0.301
71821	c	105	130	13	1.00	0.30	22	22.7	38.3	8500	14000	0.314
	ac				1.00	0.30	34	21.3	36.1	8000	13000	0.314
71822	c	110	140	16	1.00	0.30	25	31.8	51.6	8000	13000	0.496
	ac				1.00	0.30	37	29.9	48.7	7500	12000	0.496
71824	c	120	150	16	1.00	0.30	26	33.1	56.9	7000	11000	0.537
	ac				1.00	0.30	39	31.1	53.7	6700	10000	0.537
71826	c	130	165	18	1.10	0.60	29	38.7	67.6	6700	10000	0.782
	ac				1.10	0.60	43	36.3	63.8	6000	9000	0.782
71828	c	140	175	18	1.10	0.60	30	44.8	79.2	6000	9000	0.813
	ac				1.10	0.60	46	42	74.7	5600	8500	0.813
71830	c	150	190	20	1.10	0.60	33	51.2	92	5600	8500	1.140
	ac				1.10	0.60	50	48	86.8	5000	7500	1.140
71832	c	160	200	20	1.10	0.60	34	52.4	97.7	5000	7500	1.210
	ac				1.10	0.60	52	49.2	92.2	4800	7000	1.210
71834	c	170	215	22	1.10	0.60	37	66.5	123.4	4800	7000	1.610
	ac				1.10	0.60	56	62.4	116.5	4300	6300	1.610