

巴法络/BUFFALO TS-RVH12TL/R6 四盘位网络存储 NAS

产品名称	巴法络/BUFFALO TS-RVH12TL/R6 四盘位网络存储 NAS
公司名称	上海兮克网络科技有限公司
价格	16700.00/台
规格参数	品牌:BUFFALO 型号:TS-RVH12TL/R6-AP 系统内存:2GB
公司地址	中国 上海市徐汇区 漕溪北路339号百脑汇4E12室
联系电话	86 021 60857558 13564916044

产品详情

品牌	BUFFALO	型号	TS-RVH12TL/R6-AP
系统内存	2GB	硬盘盘位	4
支持RAID级别	RAID0, 1, 5, 6, 10, Normal (JBOD)	总容量	12TB
处理器	Intel Atom 1.66 GHz	支持网络标准	IEEE802.3ab / IEEE802.3u / IEEE802.3

- intel® atom™ 1.66 ghz dual core / 2 gb ram- powerful hardware makes data transfer faster. multiple pcs access is also faster- four front loading hot swap hard drives with lockable front panel- cartridge mounted hot swap hard drives behind the front panel for easy drive access and replacement- active directory support- quota support prevents users/groups from consuming too much disk space- scheduled shut down reduces energy costs- dfs (distributed file system) support- easy setup wizard and management through intuitive web interface- 10/100/1000 gigabit ethernet with jumbo frame- two ethernet ports for port trunking- supported raid levels: 0, 1, 5, 6, 10, normal (jbod)- share level replication feature synchronizes files of terastations- failover synchronizes configuration data and files between two terastation pros. when the main terastation fails, the backup terastation automatically becomes a main terastation- hot spare enables automatic raid build in case of a drive failure- optional aes-128 bit hard drive encryption- reliable fan and advanced ventilation design cool down hard drives and other components efficiently- lcd display shows important terastation information and disk status- led indicators (uid) on front and rear glow blue when either front or rear indicator button is pushed, allowing for easy maintenance of rack-mounted devices- built-in ftp server functionality- bittorrent client: download digital content from the internet directly to your terastation- dlna certified built-in media server for streaming multimedia content- 3 usb 2.0 ports and 2 usb 3.0 ports for external drive, printer and ups connectivity- 10 licenses of novabackup® business essentials backup software included. backup included: back up up to 10 windows pcs, windows servers, exchange or ms sql databases- 3-year limited warranty

model:ts-rvh4.0tl/r6 (4tb)ts-rvh8.0tl/r6 (8tb)ts-rvh12tl/r6 (12tb)

buffalo 's terastation pro™ rackmount is a high performance network storage solution ideal for businesses and demanding users looking to implement a raid based network storage solution for larger networks and business critical applications. with the powerful intel® atom™ d510 dual-core processor, terastation pro rackmount provides exceptional performance during file transfers and everyday nas functions. terastation pro rackmount runs many services simultaneously and the dual-core processor enables the ability to focus on concurrent tasks with minimal performance degradation: experience maximum network throughput while a replication job runs in the background or perform fast search indexing. terastation pro rackmount is packed with business class features such as active directory support, quota support, share level replication, failover support, dual gigabit ethernet ports, hot-swap hard drives and usb 3.0 accessory support.

lan interface

data transfer rates	10 / 100 / 1000 mbps
connector type	rj-45
number of ports	2

internal hard drives

number of drives	4
drive interface	sata 3 gb/s
hard drive sizes	1.0 tb, 2.0 tb
total capacity	4.0 tb, 8.0 tb, 12 tb
supported raid levels	0, 1, 5, 6, 10, normal

usb interface

standard compliance	usb 3.0 / usb 2.0
number of ports	2 usb 3.0 / 3 usb 2.0
data transfer rates	5 gbps* (usb 3.0)max. 480 mbps (usb 2.0)

protocol support

networking	tcp / ip
file sharing	cifs / smb, afp, http / https, ftp / ftps / sftp, nfs
directory integration	ldap
management	http / https
time synchronization	ntp

other

dimensions (wxhxd)	430 x 44.3 x 420 mm
--------------------	---------------------

rackmount height	1u
weight	9 kg
setup utility os support	windows® operating systems, mac os
client os support	windows® 7 (32-bit/64-bit) / vista® (32-bit/64-bit)xp / 2000 / server2008 / server2003 / 2000 server, mac os 10.3.9 or later
power supply	internal, ac 110-240v 50/60 hz