

再生阳图ps版 铝版

产品名称	再生阳图ps版 铝版
公司名称	江苏韵燕印刷版材有限公司
价格	.00/个
规格参数	版材:铝版
公司地址	泰兴市经济开发区高新产业园向荣路南首区间路6号
联系电话	0523-87733184 18621585920

产品详情

版材 铝版

品名：阳图ps版

product name: positive ps plate

厚度：0.15-0.30mm

thickness: 0.15-0.30mm

光源：300-400nm，300w碘镓灯，灯距1~1.2米，55-60秒

spectral sensitivity: 300-400nm,3000w iodine-gallium lamp, distance: 1~1.2m, for duration of 55-60seconds

感光度：160-180mj/cm²

laser energy required:160-180mj/cm²

网点还原：2-98%@200lpi

resolution: 2-98%@200lpi

显影温度：23 ± 2 ° c

developer temperature:23 ± 2 ° c

显影时间：30 ± 5秒

dwel time:30 ± 5seconds

保护胶：适合所有ps版保护胶

plate finisher: suitable to any ps plate finisher

烤版：220-250 ° c , 5~8分钟

backing conditions: 220-250 ° c for a duration of 5-8 minutes

耐印力：正常使用50,000~80,000印次，烤版后增加3~5倍

run length: 50,000~80,000 impressions unbaked, 250,000~400,000 impressions post-baked. actual run length may vary according to press, ink and paper conditions

安全光：黄色灯光

safe light: yellow

保质期：18个月（在建议的保存环境）

shelf life: 18 months under recommended storage conditions

包装：所有标准包装及大批量包装，0.15mm，100张/箱，0.30mm，50张/箱

package: available in all standard formats including bulk packaging options. 0.15mm, 100sheets/carton,0.30mm, 50sheets/carton

运输及储存：平放，常温下保存，相对湿度40%到70%

transport and storage: store plates flat at normal temperature with relative humidity between 40% and 70%.