

费希尔调压器67CFR fisher regulator 67CFR

产品名称	费希尔调压器67CFR fisher regulator 67CFR
公司名称	常州品顺厨房用品有限公司
价格	.00/个
规格参数	
公司地址	常州市钟楼区五星街道长江中路285号
联系电话	18136385270

产品详情

费希尔调压器67CFR fisher regulator 67CFR

67C Series direct-operated regulators and filter regulators are typically used to provide constantly controlled, reduced pressures to pneumatic and electropneumatic controllers and other instruments. These are suitable for most air or gas applications. Other applications include providing reduced pressures to air chucks, air jets, and spray guns. Body Sizes and End Connection Styles Sizes: NPS 1-1/4, NPS 1-1/2, NPS 2 / DN 50 Connections: NPT, CL125 FF Flanged, CL250 RF flanged, PN 10/16 flanged Maximum Operating Inlet Pressure by Orifice Size 1/4 x 3/8 in. / 6.4 x 9.5 mm : 175 psig / 12.1 bar 3/8 in. / 9.5 mm : 175 psig / 12.1 bar 1/2 in. / 13 mm : 175 psig / 12.1 bar 3/4 in. / 19 mm : 150 psig / 10.3 bar 7/8 in. / 22 mm : 125 psig / 8.6 bar 1 in. / 25 mm : 100 psig / 6.9 bar 1-3/16 in. / 30 mm : 80 psig / 5.5 bar Maximum Outlet (Casing) Pressure 66 psig / 4.5 bar Minimum Differential Pressure for Full Stroke 1.5 psid / 0.10 bar d Outlet Pressure Ranges 3.5-inches w.c. to 60 psig / 9 mbar to 4.14 bar in nine ranges Pressure Registration Internal, External, or Dual Registration Temperature Capabilities -20 to 150 ° F / -29 to 66 ° C Approximate Weight 21 lbs / 10 kg