

T654dn内置双面，可打印高达400g铜版纸，卡片纸等

产品名称	T654dn内置双面，可打印高达400g铜版纸，卡片纸等
公司名称	上海源普信息技术有限公司
价格	13000.00/台
规格参数	品牌:利盟 (lexmark) 型号:T654dn 涵盖功能:打印
公司地址	上海市徐汇区天钥桥路380弄20号10F室
联系电话	86 021 64383433

产品详情

品牌	利盟 (lexmark)	型号	T654dn
涵盖功能	打印	打印速度	53ppm
打印分辨率	1200*200dpi		

概述：

高可靠性的利盟t654dn是工作组级用户的理想选择，操作使用更容易、管理更方便、最高53页的打印速度，标配的双面打印帮助您节省纸张和成本。可打印a4幅面400g铜版纸等，连续供纸，稳定高效，欢迎来电垂询！

高达53页/分钟的打印速度

600mhz处理器

256mb标配内存

月推荐打印量：5,000-35,000页

550页标配纸张输出，选配后最大可以达到2,950页

随机耗材容量10,000页

后续耗材容量高达到36,000页

可在打印机上安装利盟解决方案软件

技术规格：

unspsc代码	43212105
打印速度 (a4, 黑色) : 高达	53页/每分钟
双面打印速度 (a4, 黑色) : 高达	36spm
打印速度 (letter, 黑色) : 高达	55页/每分钟
双面打印速度 (letter, 黑色) : 高达	37spm
首页打印时间 (黑色) 高达	7.5秒
打印分辨率, 黑色	1200 图像质量1200 x 1200 dpi2400 图象质量600 x 600 dpi
处理器	600mhz
内存, 标准	256mb
内存, 最大	1280mb
可扩展内存选件	yes
支持apple macintosh 操作系统	apple mac os x apple mac os 9.2
citrix metaframe	microsoft windows 2000 server running terminal services with citrix presentation server 3.0, 4.0microsoft windows server 2003 running terminal services with citrix presentation server 3.0, 4.0, 4.5 microsoft windows server 2003 x64 running terminal services with citrix presentation server 4.0 x64, 4.5 x64
支持linux 操作系统	linpus linux desktop 9.2, 9.3red hat enterprise linux ws 3.0, 4.0, 5.0suse linux enterprise server 8.0, 9.0, 10, 11suse linux enterprise desktop 10opensuse 10.2, 10.3, 11.0, 11.1inspire linux 6.0 debian gnu/linux 4.0red flag linux desktop 5.0, 6.0ubuntu 7.10ubuntu 8.04 ltssuse linux enterprise desktop 11debian gnu/linux 5.0ubuntu 8.10, 9.04
支持microsoft windows 操作系统	microsoft windows 2000microsoft windows xpmicrosoft windows server 2003microsoft windows xp x64microsoft windows server 2003 running terminal servicesmicrosoft windows 2000 server running terminal servicesmicrosoft windows server 2003 x64 microsoft windows server 2003 x64 running terminal servicesmicrosoft windows vistamicrosoft windows vista x64microsoft windows server 2008microsoft windows server 2008 x64microsoft windows server 2008 running terminal servicesmicrosoft windows server 2008 x64 running terminal servicesmicrosoft windows 7
支持novell 操作系统	novell® open enterprise server for netware with nds, iprint or novell distributed print services (ndps)novell netware 5.x, 6.x with iprint or novell distributed print services (ndps)
支持unix 操作系统	sun solaris sparc 8, 9, 10sun solaris x86 10hp-ux 11.11, 11.23, 11.31ibm aix 5.2, 5.3, 6.1
支持的其它操作系统	使用 os/400 主机打印转换的 ibm iseries 或 ibm as/400 ® 系统, 带有 tcp/ip 和 os/400 ® v3r1 或更新版本事实上支持 tcp/ip 的任意平台
纸张处理标准	integrated duplex100-sheet multipurpose feeder 550-sheet input tray 550 页接纸架
纸张处理选件	1850 页大容量接纸架带有进纸器的 200 页通用可调节进纸匣带有进纸器的 400

进纸容量 (标准)	650 页
进纸容量 (最大)	4300页
接纸架容量 (标准)	550 页
接纸架容量 (最大)	2950页
信封容量	85
装订选件?	是
进纸器数量	2
进纸器数量, 最大	6
支持的介质类型	card stock双层标签envelopes综合标签paper labelsplain paper聚酯标签transparenciesvinyl labelsrefer to the card stock & label guide
支持的介质尺寸	10 envelope7 3/4 envelope9 envelopea4a5dl envelopea6 卡片executivefoliojis-b5legalletterstatementuniversal
消耗品打印容量	25,000*页高容量打印鼓粉盒*依据iso/iec 19752的平均标定标准打印量值。 7,000*-page print cartridge36,000*-page extra high yield print cartridge
标准端口	ethernet 10/100basetx (rj-45) 一个内置式卡插槽usb 2.0 specification hi-speed certified (type b)front usb 2.0 specification hi-speed certified port (type a) rear usb 2.0 specification hi-speed certified port (type a)
可选的本地端口	internal rs-232c serialinternal 1284-b bidirectional parallel
可选的网络接口	lexmark n4050e 802.11g wireless print server (print only)external marknet™ n7020e gigabit ethernetinternal marknet™ n8120 gigabit ethernetinternal marknet™ n8130 fiber fast ethernetinternal marknet™ n8150 802.11b/g/n wireless
网络管理协议	httphttps (ssl*/tls)snmpv3winsigmpbootp, rarpapipa (auto ip)dhcpicmpdnssnmpv2cbonjourddnsmdnsarpntptelnetfi nger*this product includes software developed by the openssl project for use in the openssl toolkit.
网络协议支持	tcp/ip ipv4ipx/spxappletalk™lexlink (dlc)tcp/ip ipv6tcpudp
网络打印方法	lpr/lpddirect ip (port 9100)socket (raw tcp/ip)httpnds queue-based printingndps/neps (novell distributed print services, novell netware enterprise print services) enhanced ip (port 9400)ftp, tftpipp 1.1 (internet printing protocol)thinprint .print integration
网络安全性	snmpv3802.1x authentication: md5, mschapv2, leap, peap, tls, ttls ipsec
字体和符号集	3 of 9 scalable pcl 5e fonts in narrow, regular and wide158 scalable postscript fonts 2 pcl bitmap fonts 39 scalable ppds fonts 5 ppds bitmap fonts 84 scalable pcl fonts ocr-a, ocr-b scalable pcl 5e fonts for more information, refer to the technical reference.
打印机语言 (标准)	pcl 5e 仿真pcl 6 emulationpersonal printer data stream (ppds)postscript 3 emulationxhtmlpdf 1.6direct imagemicrosoft xps (xml paper specification)

包装尺寸 (毫米 - 高 x 宽 x 长)	550 x 625 x 545毫米
尺寸 (毫米 - 高 x 宽 x 长)	438 x 425 x 510毫米
重量 (公斤)	23.4公斤
噪声级别, 空闲时	30dba
打印噪声级别, 工作时	55dba
产品保修	1年现场服务, 第2个工作日响应
产品证书	energy star, blue angel (ral-uz-122), can/csa-c22.2 60950-1, csa e60825-1, ices-003 class b, bsmi class b, cns 13438, vcci class b, us fda, fcc class b, ul 60950-1, iec 320-1, en/iec 60320-1, ce class b, cb iec 60950-1, en 60950-1, en/iec 61000-3, en 55022 class b, en 55024, en/iec 60825-1, gs (t ü v), semko, ul ar, cs, t ü v rh, sma c-tick mark class b, ccc class b, cispir 22 class b, ek mark, n mark
duty cycle notes	"recommended monthly page volume" is a range of pages that helps customers evaluate lexmark ' s product offerings based on the average number of pages customers plan to print on the device each month. lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage."maximum monthly duty cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. this metric provides a comparison of robustness in relation to other lexmark printers and mfps.
指定操作环境	temperature: 16 to 32 ° c (60 to 90 ° f)humidity: 8 to 80% relative humidityaltitude: 0 - 3048 meters (10,000 feet)