

金属软管技术参数

类别	公称内径	最小内径	最大外径	工作压力		试验压力	爆破压力	最小弯曲半径	
				mpa	psi			静态	动态
高压	4681012	2.54.56.58.510	8.512141620	35	5071	1.5pn	3pn	100n	2rj
	1418202532	1216182230	2226283442	211715107	30432463217514491014				
中压	46810	2.54.56.58.5	8.512.514.516.4	10	1449	4pn			
	121418	121418	202226	8.0	1159				
	2025	2024	2834	6.4	927				
	3240	3240	4252	4.0	579				
低压	46810	46810	8.5121416	2.5	362				
	12141820	12141820	20222628	1.6	231				
	2532	2432	3442	1.0	144				
	4050	4050	5264	2.5	362				
	75100	75102	92122	1.6	231				
	125150	125150200250	161193252302	1.0	144				
	200250			0.8	116				

普通型波纹管

产品构造

公称压力pnmpa	公称 口径 mm	产品代号	螺纹连接尺寸		最小弯曲半径		试验压力ps mpa	供货长度m		
			螺纹m	六方s	静态rj	动态rd				
高压g	35	4	jrg4-l	m12 × 1.5	17	10d n	2rj	1.5pn	200-1600	
	23	6	jrg6-l	m14 × 1.5	19					
		8	jrg8-l	m16 × 1.5						
		10	jrg10-l	m20 × 1.5						
		12	jrg15-l	m22 × 1.5						
	21	15	jrg15-l	m24 × 1.5	27					200-2100
	16	18	jrg18-l	m30 × 1.5	36					250-2100
20		jrg20-l								
中压g	10	4	jrz4-l	m12 × 1.2 5	17			1.5pn	200-1600	
		6	jrz6-l	m14 × 1.5						
		8	jrz8-l	m16 × 1.5	19					
		10	jrz10-l	m20 × 1.5	24					
	8	12	jrz12-l	m22 × 1.5	27				200-2100	
		15	jrz15-l	m24 × 1.5	36				250-2100	
		18	rz18-l	m30 × 1.5						
	6.4	20	jrz20-l							
25		jrz25-l	m36 × 1.5	41	260					

	4	32	jrz32-l	m45 × 1.5	50				350
低压g	2.5	4	jrd4-l	m12 × 1.2 5	17				200 - 1600
		6	jrd6-l	m14 × 1.5					
		8	jrd8-l	m16 × 1.5	19				
		10	jrd10-l	m20 × 1.5	24				
		12	jrd12-l	m22 × 1.5	27				
	1.6	15	jrd15-l	m24 × 1.5				200 - 1200	
		18	jrd18-l	m30 × 1.5	36			250 - 2100	
		1	20	jrd20-l					
	25		jrd25-l	m36 × 1.5	41			260	
	32		jrd32-l	m45 × 1.5	50			350	
产品代号标记 示例	内锥或球形接头，公称通径20mm,公称压力16mpa,长度1500mm的金属软管，产品代号为16jrg20 - 1500如果接头形式采用一头内锥，一头球头以及其它的连接形式，订货时请注明。								