

GPS/GSM组合天线 GPS/GSM

产品名称	GPS/GSM组合天线 GPS/GSM
公司名称	嘉兴市穿云电子科技有限公司
价格	.00/个
规格参数	品牌:GPS/GSM 型号:GPS/GSM-02 增益:3
公司地址	嘉兴市东栅经济园纬一西路101号综合楼B幢
联系电话	13362302892

产品详情

品牌	GPS/GSM	型号	GPS/GSM-02
增益	3	频率范围	5 (MHz)

(i) dielectric antennacenter frequency 1575.42mhz \pm 3 mhzv.s.w.r 1.5:1band width \pm 5 mhzimpedance 50 ohmpeak gain > 3dbic based on 7 \times 7cm ground planegain coverage > -4dbic at $-90^\circ < 0 < +90^\circ$ (over 75% volume)polarization rhcp (ii) gsm antennacenter frequency 850/900/1800/1900mhztypical gain2dbi+/-1db@850mhz2dbi+/-1db@900mhz1dbi+/-1db@1800mhz;1dbi+/-1db@1900mhzv.s.w.r 2.0:1impedance 50 ohm (iii) Ina/filterIna gain(without cable) 28db typicalnoise figure 1.5dbfilter out band attenuation (f0=1575.42 mhz)7db min f0+/-20mhz ;20db min f0+/-50mhz;30db min f0+/-100mhzv.s.w.r < 2.0dc voltage 2.7v/3.0v/3.3v/5.0v/3.0v to 5.0v/otherdc current 11ma max (iv) mechanicalweight < 240gramsize 80 mm(d) \times 13mm(h)cable gps-----rg174 2meter, 5meter long or othergsm-----rg174 2meter, 5meter long or otherconnector gps-----sma/smb/smc/bnc/fme/tnc/mcx /mmc or othergsm-----sma/smb/smc/bnc/fme/tnc/mcx/mmc or othermounting adhesive /magnetic/screw mountinghousing black (v) environmentalworking temp. -40 ~+85 storage temp. -45 ~+100 vibration sine sweep 1g(0-p)10~50~10hz each axishumidity humidity95%~100%rhweatherproof 100%waterproof